

| Project name: | |
|---------------|--|
| Fixture type: | |
| Date: | |

4" Square Die-Cast Baffle Trim



Features

- Square Trim Die-Cast Baffle.
- Lamp: 50W MAX PAR20.
- O.D.: 4 3/4" Square.

Technical Details


Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



| _ |
|---|
| |
| |

Compatible Products



For use with 4" Trims for PAR Lamps

4" Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**




4" Airtight IC Housing **New Construction**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99ICA | Lamp: 50W MAX. |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99A | Lamp: 50W MAX. |

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction**



4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| EL99ICA-G24 | Lamp: 18W MAX. |

| CAT NO. | SPECIFICATIONS | |
|----------|----------------|--|
| EL99FICA | Lamp: 35W MAX. | |

4" Accessories

CAT NO.

FIRECVR



Fire Cover

SPECIFICATIONS

9 3/4" H x 17" O.D.







| CAT NO. | SPECIFICATIONS |
|------------|---------------------------|
| FIREENCL | 20 3/8" L x 14 3/8" W |
| FIREENCL-S | Shallow, 16" L x 14 3%" W |

Mica Fire Tape

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3⁄4" W x 16' L |