

4" Stepped Phenolic Deep Baffle with Die-Cast Ring Trim



Features

- Phenolic Step Baffle.
- Lamp: 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Diecast trim ring for durability and lasting quality.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4" Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Product Numbers

| Item | Finish |
|---------|-----------|
| EL994DW | All White |

Compatible Products

For use with 4" Trims for PAR Lamps

4" Line Voltage ICA Housings



4" Airtight IC Housing
Double Wall Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99ICA | Lamp: 50W MAX. |



4" Airtight Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99A | Lamp: 50W MAX. |



4" Airtight IC Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------|
| EL99LDICA | Lamp: LED 12W MAX. |



4" Airtight IC Housing with GU24 Base Socket
New Construction

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| EL99ICA-G24 | Lamp: 18W MAX. |



4" Airtight IC 2-Hour Fire Rated Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| EL99FICA | Lamp: 35W MAX. |

4" Accessories



Fire Cover

| CAT NO. | SPECIFICATIONS |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |



Fire Enclosure

| CAT NO. | SPECIFICATIONS |
|------------|----------------------------|
| FIREENCL | 20 3/8" L x 14 3/8" W |
| FIREENCL-S | Shallow, 16" L x 14 3/8" W |



Mica Fire Tape

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |