

Project name:

Fixture type:

Date:

# 5" Airtight IC Housing with GU24 Socket for Ketra



## Dimensions



- Airtight Housing for insulated ceilings.
- Lamp: GU24

Features

- Compatible with the Ketra S30 Downlight Trim
- Meets CA Title 24 standards with qualified lamps.
- UL Listed for damp location and for feed through.

## **Technical Details**

#### Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Aluminum housing for greater heat dissipation. Stamped galvanized steel frame.

**Installation:** Designed for ceiling plenums where 2x8 joists or taller are used. High strength hanger bars can easily be nailed to joists. Maximum hole cutout is 5 1/2". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size pryout conduit knockouts, 4 Romex pryouts with strain relief.

**Hanger Bars:** Pre-installed hanger bars with True Nail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-grids. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housing with the joists.

#### Electrical:

- Input Voltage: 120V AC.
- Thermally protected against improper lamping.

Trims: Compatible with the Ketra S30 Downlight Trim.

#### Listings:

- UL Listed for Damp Location.
- UL Listed for Feed Through.
- UL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.


Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

Voltage	120V	
Lamp Type	GU24	
Damp Location Listed		

2714

Specifications

Wattawa



### **Product Number**

Item	Lamp type	Watts	Voltage	
LUT-EL5ICA-G24	GU24	27W	120V	

5 16

7 3/8

4