

Project name:	
Fixture type:	
Date:	

5" Dedicated LED IC Airtight Remodel Housing




Features

- Single wall IC remodel construction, for use in insulated ceilings.
- CA Title 24 compliant (as high efficiency luminaire).
- Trims sold separately.
- Lamp: 17W Max 120V.
- cUL Listed for damp location and for feed through.
- Compatible with ELCO 5" LED Inserts.

Specifications

Wattage	17W
Voltage	120V
Damp Location Listed	

Dimensions



Technical Details

Construction:

- · Single wall IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- · Steel housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller joists are used. Maximum hole cutout is 5 1/2". See installation sheet for detailed information.

Electrical:

- Input Voltage: 120V AC.
- Inherently protected.

Dimmability:

• Dimmability based on lamp.

Lamp: Designed for use with ELCO 5" LED inserts, LED modules, or PSA37 with 5" MR16 trims.

Listings:

- · cUL Listed for Damp Location.
- · cUL Listed for Wet Location with select trims.
- · cUL Listed for Feed Through.
- · cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

Product Numbers

Item	Watts	Voltage	
EL570RICA	17W	120V	

Compatible Products



For use with Dedicated 5" Dedicated IC LED Housings

5" LED Inserts



Round Reflector

CAT NO.	SPECIFICATIONS
EL61527W, BZ	10W, 800 lm, 2700K
EL61530W, BZ	10W, 850 lm, 3000K
EL61535W, BZ	10W, 900 lm, 3500K
EL61540W	10W, 900 lm, 4000K
EL61550W	10W, 950 lm, 5000K
EL615CT5W, BZ	12W, 880 lm - 1080 lm, 2700K - 5000K CCT switch



Round Reflector

CAT NO.	SPECIFICATIONS
EL61727W	14W, 1000 lm, 2700K
EL61730W	14W, 1000 lm, 3000K
EL61735W	14W, 1100 lm, 3500K
EL61740W	14W, 1200 lm, 4000K
EL617CT5W	12W, 880 lm - 1080 lm, 2700K - 5000K CCT SWITCH
LLOI/CISW	2700K - 5000K CCTswitch



Round Reflector

CAT NO.	SPECIFICATIONS
EL62727W	20W, 1400 lm, 2700K
EL62730W	20W, 1400 lm, 3000K
EL62735W	20W, 1500 lm, 3500K
EL62740W	20W, 1600 lm, 4000K



Round Deep Reflector

CAT NO.	SPECIFICATIONS
EL62527W, C, H	14W, 1000 lm, 2700K
EL62530W, C, H	14W, 1000 lm, 3000K
EL62535W, C, H	14W, 1100 lm, 3500K
EL62540W, C, H	14W, 1200 lm, 4000K
EL625CT5W	12W, 840 lm - 1100 lm, 2700K - 5000K CCT



DIMS TO WARM

Round Insert

CAT NO.	SPECIFICATIONS
EL615SDW, BZ	10W, 750 lm, Sunset, Reflector
EL610SDW, BZ	10W, 750 lm, Sunset, Baffle



Round Baffle

CAT NO.	SPECIFICATIONS
EL61027W	10W, 800 lm, 2700K
EL61030W	10W, 850 lm, 3000K
EL61040W	10W, 900 lm, 4000K
EL610CT5W	12W, 880 lm - 1080 lm, 2700K - 5000K CCT switch



Round Baffle

CAT NO.	SPECIFICATIONS
EL61130W	14W, 1000 lm, 3000K
EL61140W	14W, 1200 lm, 4000K
EL611CT5W	14W, 850 lm - 1400 lm, 2700K - 5000K CCTSWITCH





Round Baffle

CAT NO.	SPECIFICATIONS
EL61230W	20W, 1400 lm, 3000K
EL612CT5W	12W, 850 lm - 1400 lm, 2700K - 5000K CCT



Round Gimbal

SPECIFICATIONS
13W, 930 lm, 2700K
13W, 950 lm, 3000K

*Finishes: W - All White, BZ - All Bronze, C - Chrome w/White Ring, H - Haze w/White Ring

Compatible Products



For use with Dedicated 5" Dedicated LED IC LED Housings

5" LED Inserts



Round Deep Baffle

CAT NO.	SPECIFICATIONS
EL62127W	14W, 1000 lm, 2700K
EL62130W	14W, 1000 lm, 3000K



Square Reflector

CAI NO.	SPECIFICATIONS
EL55230W	16W, 1300 lm, 3000K



Square Baffle

CAT NO.	SPECIFICATIONS	
EL55130W	16W 1300 lm 3000K	



Round Pull Down Adjustable

CAT NO.	SPECIFICATIONS
EL59727W, B, BZ	12.6W, 800 lm, 2700K
EL59730W. B. BZ	12.6W. 840 lm. 3000K

5" Accessories



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 ³ / ₄ " H × 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 ¾" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS	
FIRETAPE	3/4" W × 16' L	



Cover Plate Color Trims

CAT NO.	SPECIFICATIONS
RMLD6B	Black
RMLD6BZ	Bronze
RMLD6C	Chrome

^{*}Finishes: W - All White, B - All Black, BZ - All Bronze, C - Chrome w/White Ring, H - Haze w/White Ring