

Project name:

Fixture type:

Date:

Specifications

Damp Location Listed

17W

120V

Wattage

Voltage

5" Dedicated LED IC Airtight Remodel Housing



Features

- Single wall IC remodel construction, for use in insulated ceilings.
- CA Title 24 compliant (as high efficiency luminaire).
- Trims sold separately.
- Lamp: 17W Max 120V.
- cUL Listed for damp location and for feed through.
- Compatible with ELCO 5" LED Inserts.

Technical Details

Construction:

- Single wall IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
 Steel housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller joists are used. Maximum hole cutout is 5 1/2". See installation sheet for detailed information.

Electrical:

- Input Voltage: 120V AC.
- Inherently protected.

Dimmability:

• Dimmability based on lamp.


Lamp: Designed for use with ELCO 5" LED inserts, LED modules, or PSA37 with 5" MR16 trims.

Listings:

- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.Install a JA8-2016-E lamp for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

Dimensions



Product Number

Item	Watts	Voltage
EL570RICA	17W	120V

Compatible Products

For use with Dedicated 5" Dedicated IC LED Housings

5" LED Inserts

Ro	und Reflector		Cound Reflector	EXTRA STA HIGHLUMEN	Roun
CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPE
EL61527W, BZ	10W, 800 lm, 2700K	EL61727W	14W, 1000 lm, 2700K	EL62727W	20
EL61530W, BZ	10W, 850 lm, 3000K	EL61730W	14W, 1000 lm, 3000K	EL62730W	20
EL61535W, BZ	10W, 900 lm, 3500K	EL61735W	14W, 1100 lm, 3500K	EL62735W	20
EL61540W	10W, 900 lm, 4000K	EL61740W	14W, 1200 lm, 4000K	EL62740W	20
EL61550W	10W, 950 lm, 5000K	EL617CT5W	12W, 880 lm - 1080 lm, 2700K - 5000K CCTswich		
EL615CT5W, BZ	12W, 880 lm - 1080 lm, 2700K - 5000K				



Round Reflector		
CAT NO.	SPECIFICATIONS	
EL62727W	20W, 1400 lm, 2700K	
EL62730W	20W, 1400 lm, 3000K	
EL62735W	20W, 1500 lm, 3500K	
EL62740W	20W, 1600 lm, 4000K	

EL ELCO Lighting

HIGHLUMEN	
I HOITEONIEI 4	
·	



Round Deep Reflector

CAT NO.	SPECIFICATIONS
EL62527W, C, H	14W, 1000 lm, 2700K
EL62530W, C, H	14W, 1000 lm, 3000K
EL62535W, C, H	14W, 1100 lm, 3500K
EL62540W, C, H	14W, 1200 lm, 4000K
EL625CT5W	12W, 840 lm - 1100 lm, 2700K - 5000K



Round Baffle	
CAT NO.	SPECIFICATIONS
EL61130W	14W, 1000 lm, 3000K
EL61140W	14W, 1200 lm, 4000K
EL611CT5W	14W, 850 lm - 1400 lm, 2700K - 5000K



DIMS TO WARM **Round Insert**

CAT NO.	SPECIFICATIONS
EL615SDW, BZ	10W, 750 lm, Sunset, Reflec- tor
EL610SDW, BZ	10W, 750 lm, Sunset, Baffle



Round Baffle CAT NO. SPECIFICATIONS EL61027W 10W, 800 lm, 2700K EL61030W 10W, 850 lm, 3000K EL61040W 10W, 900 lm, 4000K 12W, 880 lm - 1080 lm, EL610CT5W 2700K - 5000K CCTsw



Round Baffle

CAT NO.	SPECIFICATIONS
EL61230W	20W, 1400 lm, 3000K
EL612CT5W	12W, 850 lm - 1400 lm, 2700K - 5000K CCTSWICH



Round Gimbal CAT NO. SPECIFICATIONS EL61627W 13W, 930 lm, 2700K EL61630W 13W, 950 lm, 3000K

*Finishes: W - All White, BZ - All Bronze, C - Chrome w/White Ring, H - Haze w/White Ring

Compatible Products

For use with Dedicated 5" Dedicated LED IC LED Housings

ELCO Lighting

5" LED Inserts

HIGHLUMEN			Jak -
1	Round Deep Baffle		Square Reflector
CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS



EL5513

EL62127W 14W, 1000 lm, 2700K EL62130W 14W, 1000 lm, 3000K



16W, 1300 lm, 3000K

	Square Baffle
CAT NO.	SPECIFICATIONS
EL55130W	16W, 1300 lm, 3000K



Round Pull Down Adjustable

CAT NO.	SPECIFICATIONS
EL59727W, B, BZ	12.6W, 800 lm, 2700K
EL59730W, B, BZ	12.6W, 840 lm, 3000K

5" Accessories

Emergency Battery Backup		Fire Cover		Fire Enclosure	
CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V Mica Fire Tape	FIRECVR	9 ¾" H x 17" O.D.	FIREENCL FIREENCL-S	20 ⅔" L x 14 ⅔" W Shallow, 16″ L x 14 ⅔" W
CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS		
FIRETAPE	³⁄4″ W × 16′ L	RMLD6B RMLD6BZ	Black Bronze		

*Finishes: W - All White, B - All Black, BZ - All Bronze, C - Chrome w/White Ring, H - Haze w/White Ring

Chrome

RMLD6C