


5" New Construction 2-Hour Fire Rated IC Housing

5" 2-hour fire rated new construction LED housing with quick connect.




Features

- Double Wall New Construction IC Housing.
- cUL Listed for 2-Hour Fire Resistance to meet and exceed strict fire safety codes.
- Integrated Non-combustible insulation acts as a sound barrier minimizing sound transfer between floors.
- Meets Title 24 requirements. ENERGY STAR® Certified.
- STC/IIIC Sound Rated
- Trims and inserts sold separately.

Specifications

| | |
|----------------------|--------------|
| Wattage | 22W |
| Voltage | 120V or 277V |
| Damp Location | Listed |

Dimensions



Technical Details

Construction:

- Double wall IC rated for direct contact with insulation. For use in IC and non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- For use with ceiling constructions: L505, L511, L536, L538, L541, L556, L577, M500, M510, M521, and M543.

Installation:

- Designed for ceiling plenums where 2x8 joists or taller are used.
- High strength hanger bars can easily be nailed to joists.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Hanger Bars: Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- Inherently protected.

Emergency Battery Pack: Optional 90 minute battery pack available with test indicator switch. Note that double wall housings require Access From Above Ceiling for Battery Maintenance.

Listings: cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Direct Contact with Insulation and Combustible Material. cUL Listed for Feed Through. Sound rated.

Product Numbers

| Item | Description | Watts | Voltage |
|-------------------|----------------------------|-------|---------|
| EL56FICA | | 22W | 120V |
| EL56FICA-7 | with Step-down Transformer | 22W | 277V |

Compatible Products

For use with Dedicated 5" Dedicated IC LED Housings

5" LED Inserts



Round Reflector

| CAT NO. | SPECIFICATIONS |
|---------------|--------------------------------------|
| EL61527W, BZ | 10W, 800 lm, 2700K |
| EL61530W, BZ | 10W, 850 lm, 3000K |
| EL61535W, BZ | 10W, 900 lm, 3500K |
| EL61540W | 10W, 900 lm, 4000K |
| EL61550W | 10W, 950 lm, 5000K |
| EL615CT5W, BZ | 12W, 880 lm - 1080 lm, 2700K - 5000K |



Round Reflector

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------------------------|
| EL61727W | 14W, 1000 lm, 2700K |
| EL61730W | 14W, 1000 lm, 3000K |
| EL61735W | 14W, 1100 lm, 3500K |
| EL61740W | 14W, 1200 lm, 4000K |
| EL617CT5W | 12W, 880 lm - 1080 lm, 2700K - 5000K |



Round Reflector

| CAT NO. | SPECIFICATIONS |
|----------|---------------------|
| EL62727W | 20W, 1400 lm, 2700K |
| EL62730W | 20W, 1400 lm, 3000K |
| EL62735W | 20W, 1500 lm, 3500K |
| EL62740W | 20W, 1600 lm, 4000K |



Round Deep Reflector

| CAT NO. | SPECIFICATIONS |
|----------------|--------------------------------------|
| EL62527W, C, H | 14W, 1000 lm, 2700K |
| EL62530W, C, H | 14W, 1000 lm, 3000K |
| EL62535W, C, H | 14W, 1100 lm, 3500K |
| EL62540W, C, H | 14W, 1200 lm, 4000K |
| EL625CT5W | 12W, 840 lm - 1100 lm, 2700K - 5000K |



Round Insert

| CAT NO. | SPECIFICATIONS |
|--------------|--------------------------------|
| EL615SDW, BZ | 10W, 750 lm, Sunset, Reflector |
| EL610SDW, BZ | 10W, 750 lm, Sunset, Baffle |



Round Baffle

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------------------------|
| EL61027W | 10W, 800 lm, 2700K |
| EL61030W | 10W, 850 lm, 3000K |
| EL61040W | 10W, 900 lm, 4000K |
| EL610CT5W | 12W, 880 lm - 1080 lm, 2700K - 5000K |



Round Baffle

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------------------------|
| EL61130W | 14W, 1000 lm, 3000K |
| EL61140W | 14W, 1200 lm, 4000K |
| EL611CT5W | 14W, 850 lm - 1400 lm, 2700K - 5000K |



Round Baffle

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------------------------|
| EL61230W | 20W, 1400 lm, 3000K |
| EL612CT5W | 12W, 850 lm - 1400 lm, 2700K - 5000K |



Round Gimbal

| CAT NO. | SPECIFICATIONS |
|----------|--------------------|
| EL61627W | 13W, 930 lm, 2700K |
| EL61630W | 13W, 950 lm, 3000K |

*Finishes: **W** - All White, **BZ** - All Bronze, **C** - Chrome w/White Ring, **H** - Haze w/White Ring

Compatible Products

For use with Dedicated 5" Dedicated LED IC LED Housings

5" LED Inserts



Round Deep Baffle

| CAT NO. | SPECIFICATIONS |
|----------|---------------------|
| EL62127W | 14W, 1000 lm, 2700K |
| EL62130W | 14W, 1000 lm, 3000K |



Square Reflector

| CAT NO. | SPECIFICATIONS |
|----------|---------------------|
| EL55230W | 16W, 1300 lm, 3000K |



Square Baffle

| CAT NO. | SPECIFICATIONS |
|----------|---------------------|
| EL55130W | 16W, 1300 lm, 3000K |



Round Pull Down Adjustable

| CAT NO. | SPECIFICATIONS |
|-----------------|----------------------|
| EL59727W, B, BZ | 12.6W, 800 lm, 2700K |
| EL59730W, B, BZ | 12.6W, 840 lm, 3000K |

5" Accessories



Emergency Battery Backup

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| KEM-LD5 | 8W, 120/277V |



Cover Plate Color Trims

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| RMLD6B | Black |
| RMLD6BZ | Bronze |
| RMLD6C | Chrome |

*Finishes: **W** - All White, **B** - All Black, **BZ** - All Bronze, **C** - Chrome w/White Ring, **H** - Haze w/White Ring