

6" 0-10V IC Remodel Dedicated LED Housing




Features

- Wired for 0-10V Dimming
- Single Wall IC Airtight rated for direct contact with insulation
- 120/277V Input
- Meets restricted air flow requirements (per ASTM E-283)
- cUL listed for direct contact with insulation
- cUL listed for wet locations with wet location inserts
- cUL listed for feed through
- CA Title 24 compliant

Specifications

Voltage	120/277V
Dimmable	0-10V/Triac/ELV
Lamp Type	LED

Dimensions



Technical Details

Construction:

- Shallow Single wall IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x6 joists or taller joists are used. Maximum hole cutout is 6 1/2". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts, four 3/4" knockouts with pry-out slots. 4 Romex pryouts with strain relief.

Electrical: Input Voltage: 120/277V. Inherently protected.

Trims: Compatible with ELCO 6" 0-10V LED Inserts and 0-10V Koto™ Module

Dimmability: Dimmability based on lamp.

Listings:

- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

Product Number

Item	Lamp type	Voltage	Dimming
EL770RICDXA	LED	120/277V	0-10V/Triac/ELV

Compatible Products



For use with Dedicated 6" IC LED Housings

6" Ply™ 0-10V Dimmable, 120/277V LED Inserts



Round Insert

EL695

Finishes:

(DW, DHW, DCW)

PRODUCT NUMBER BUILDER			
6" 120/277V LED Inserts	Color Temperature		Finish
EL695			
	30	3000K (1350 lm)	DW All White
	35	3500K (1425 lm)	DHW Haze w/White Ring
	40	4000K (1500 lm)	DCW Chrome w/White Ring

6" Ply™ 0-10V Dimmable, 120/277V Adjustable LED Inserts



Round Adjustable Pull Down

EL697

Finishes:

(DXW, DXB, DXBZ, DXN)

ACCESSORIES



Interchangeable Lens
(For EL697 Series only)


EP710C 20° Beam
EP712C 60° Beam

PRODUCT NUMBER BUILDER			
6" 120/277V Adjustable LED Inserts	Style	Color Temperature	Finish
EL6			
	97 Round Adjustable	27D 2700K (850 lm)	DXW All White
		30D 3000K (900 lm)	DXB All Black
			DXBZ All Bronze
			DXBN All Nickel

Compatible Products

For use with Dedicated 6" 0-10V Koto ICAD LED Housings

0-10V Koto™ LED Module



0-10V Koto™
LED Module
ELK10DX

PRODUCT NUMBER BUILDER				
0-10V Koto™ LED Module	Lumens	Voltage	Color Temperature	Beam Angle
ELK				
	10 1000 lm	DX 120/277V	27 2700K	(blank) 38° lens (Standard)
			30 3000K	-S 18° lens
			35 3500K	-N 25° lens
			40 4000K	-W 60° lens
			SD Sunset Dimming	

ACCESSORIES



Lens

- EP731C 18° Lens
 - EP732C 25° Lens
 - EP733C 38° Lens
 - EP734C 60° Lens
- *EP732C, EP733C, EP734C Included



Snoot


- L50W White
- L50B Black



Secondary Optics

- L45 Hex Louver
- L46 Linear Lens
- L47 Spread Louver
- L49 Frosted Lens
- L51 Color Shifter

6" Twist-On Trims




Round Deep Reflector

ELK6418

Finishes:

(W, BB, BZ, H)



Round Reflector

ELK610

Finishes:

(WW, BB, BZBZ, BW, CC, CW, CN, HW)



Adj. Round Reflector

ELK629

Finishes:

(WW, BB, BZBZ, BW, CW, HW)




Adj. Round Baffle

ELK693

Finishes:

(WW, BB, BZBZ, BW)




Adj. Slot Aperture

ELK6420

Finishes:

(W)

6" Unique™ Twist-On Trims




Round Reflector

ELK6710

Finishes:

(W, B, BZ)



Round Baffle

ELK6713

Finishes:

(W, BZ)




Round Wall Wash

ELK6715

Finishes:

(W, BZ)

6" Accessories



Emergency Battery Backup

CAT NO. SPECIFICATIONS

KEM-LD5 8W, 120/277V

* Requires access from above



Fire Cover

CAT NO. SPECIFICATIONS

FIRECVR 9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO. SPECIFICATIONS

FIREENCL 20 3/8" L x 14 3/8" W

FIREENCL-S Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO. SPECIFICATIONS

FIRETAPE 3/4" W x 16' L