

# 6" 0-10V Shallow Remodel Dedicated LED Housing




## Features

- Wired for 0-10V Dimming
- Airtight rated
- 120/277V Input
- Meets restricted air flow requirements (per ASTM E-283)
- Shallow for Non-IC Application

## Specifications

<b>Voltage</b>	120/277V
<b>Dimmable</b>	0-10V/Triac/ELV
<b>Lamp Type</b>	LED

## Dimensions



## Product Numbers

Item	Lamp type	Voltage	Dimming
EL760RICDXA	LED	120/277V	0-10V/Triac/ELV

# Compatible Products



For use with Dedicated 6" IC LED Housings

## 6" Ply™ 0-10V Dimmable, 120/277V LED Inserts



**Round Insert**

**EL695**

Finishes:

(DW, DHW, DCW)

PRODUCT NUMBER BUILDER			
6" 120/277V LED Inserts	Color Temperature		Finish
<b>EL695</b>			
	<b>30</b>	3000K (1350 lm)	<b>DW</b> All White
	<b>35</b>	3500K (1425 lm)	<b>DHW</b> Haze w/White Ring
	<b>40</b>	4000K (1500 lm)	<b>DCW</b> Chrome w/White Ring

## 6" Ply™ 0-10V Dimmable, 120/277V Adjustable LED Inserts



**Round Adjustable Pull Down**

**EL697**

Finishes:

(DXW, DXB, DXBZ, DXN)

### ACCESSORIES



**Interchangeable Lens**  
(For EL697 Series only)


**EP710C** 20° Beam  
**EP712C** 60° Beam

PRODUCT NUMBER BUILDER			
6" 120/277V Adjustable LED Inserts	Style	Color Temperature	Finish
<b>EL6</b>			
	<b>97</b> Round Adjustable	<b>27D</b> 2700K (850 lm)	<b>DXW</b> All White
		<b>30D</b> 3000K (900 lm)	<b>DXB</b> All Black
			<b>DXBZ</b> All Bronze
			<b>DXBN</b> All Nickel

# Compatible Products

For use with Dedicated 6" 0-10V Koto ICAD LED Housings

## 0-10V Koto™ LED Module



0-10V Koto™  
LED Module  
ELK10DX

PRODUCT NUMBER BUILDER				
0-10V Koto™ LED Module	Lumens	Voltage	Color Temperature	Beam Angle
ELK				
	10 1000 lm	DX 120/277V	27 2700K	(blank) 38° lens (Standard)
			30 3000K	-S 18° lens
			35 3500K	-N 25° lens
			40 4000K	-W 60° lens
			SD Sunset Dimming	

### ACCESSORIES



#### Lens

- EP731C 18° Lens
  - EP732C 25° Lens
  - EP733C 38° Lens
  - EP734C 60° Lens
- \*EP732C, EP733C, EP734C Included



#### Snoot


- L50W White
- L50B Black



#### Secondary Optics

- L45 Hex Louver
- L46 Linear Lens
- L47 Spread Louver
- L49 Frosted Lens
- L51 Color Shifter


## 6" Twist-On Trims



Round Deep Reflector

ELK6418

Finishes:  
(W, BB, BZ, H)



Round Reflector

ELK610

Finishes:  
(WW, BB, BZBZ, BW, CC, CW, CN, HW)



Adj. Round Reflector

ELK629


Finishes:  
(WW, BB, BZBZ, BW, CW, HW)



Adj. Round Baffle

ELK693

Finishes:  
(WW, BB, BZBZ, BW)



Adj. Slot Aperture

ELK6420

Finishes:  
(W)


## 6" Unique™ Twist-On Trims



Round Reflector

ELK6710

Finishes:  
(W, B, BZ)



Round Baffle

ELK6713

Finishes:  
(W, BZ)




Round Wall Wash

ELK6715

Finishes:  
(W, BZ)

## 6" Accessories



Emergency Battery Backup

CAT NO. SPECIFICATIONS

KEM-LD5 8W, 120/277V

\* Requires access from above



Fire Cover

CAT NO. SPECIFICATIONS

FIRECVR 9 3/4" H x 17" O.D.




Fire Enclosure

CAT NO. SPECIFICATIONS

FIREENCL 20 3/8" L x 14 3/8" W

FIREENCL-S Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO. SPECIFICATIONS

FIRETAPE 3/4" W x 16' L