ELCO Lighting

Project name:

Fixture type:

Date:

6" 0-10V Shallow Remodel Dedicated LED Housing

Features

- Wired for 0-10V Dimming
- Airtight rated
- 120/277V Input
- Meets restricted air flow requirements (per ASTM E-283)
- Shallow for Non-IC Application

Specifications

Voltage	120/277V
Dimmable	0-10V/Triac/ELV
Lamp Type	LED

Dimensions



Product Numbers

Item	Lamp type	Voltage	Dimming
EL760RICDXA	LED	120/277V	0-10V/Triac/ELV

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2024. All rights reserved • Rev. 31 May 2023 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with Dedicated **6″ IC LED Housings**

6″ Ply™ 0-10V Dimmable, 120/277V LED Inserts

Round Insert

EL695
Finishes:
(DW, DHW, DCW)

PRODUCT NUMBER BUILDER

6″ 120/277V LED Inserts	Color Temperature		Finish	
EL695	**30**	3000K (1350 lm)	**DW**	All White
	35	3500K (1425 lm)	**DHW**	Haze w/White Ring
	40	4000K (1500 lm)	**DCW**	Chrome w/White Ring

6″ Ply™ 0-10V Dimmable, 120/277V Adjustable LED Inserts

Round Adjustable Pull Down

EL697
Finishes:
(DXW, DXB, DXBZ, DXN)

ACCESSORIES

Interchangeable Lens
(For EL697 Series only)

EP710C	20° Beam
EP712C	60° Beam

PRODUCT NUMBER BUILDER

6″ 120/277V Adjustable LED Inserts	Style		Color Temperature		Finish	
EL6	**97**	Round Adjustable	**27D**	2700K (850 lm)	**DXW**	All White
			30D	3000K (900 lm)	**DXB**	All Black
					DXBZ	All Bronze
					DXBN	All Nickel

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2024. All rights reserved • Rev. 31 May 2023 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with Dedicated **6″ 0-10V Koto ICAD LED Housings**

0-10V Koto™ LED Module



0-10V Koto™
LED Module
ELK10DX

PRODUCT NUMBER BUILDER

0-10V Koto™ LED Module	Lumens	Voltage	Color Temperature	Beam Angle
ELK				
	10 1000 lm	**DX** 120/277V	**27** 2700K	**(blank)** 38° lens (Standard)
			30 3000K	**-S** 18° lens
			35 3500K	**-N** 25° lens
			40 4000K	**-W** 60° lens
			SD Sunset Dimming	

ACCESSORIES

Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens

*EP732C, EP733C, EP734C Included

Snoot

L50W White
L50B Black



Secondary Optics

L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter

6″ Twist-On Trims



Round Deep Reflector

ELK6418
Finishes:
(W, BB, BZ, H)



Round Reflector

ELK610
Finishes:
(WW, BB, BZBZ, BW, CC, CW, CN, HW)

Adj. Round Reflector

ELK629
Finishes:
(WW, BB, BZBZ, BW, CW, HW)



Adj. Round Baffle

ELK693
Finishes:
(WW, BB, BZBZ, BW)



Adj. Slot Aperture

ELK6420
Finishes:
(W)

6″ Unique™ Twist-On Trims



Round Reflector

ELK6710
Finishes:
(W, B, BZ)



Round Baffle

ELK6713
Finishes:
(W, BZ)

Round Wall Wash

ELK6715
Finishes:
(W, BZ)

6″ Accessories



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V

* Requires access from above

Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾″ H x 17″ O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 ⅜″ L x 14 ⅜″ W
FIREENCL-S	Shallow, 16″ L x 14 ⅜″ W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	¾″ W x 16′ L

© ELCO Lighting 2024. All rights reserved • Rev. 31 May 2023 • ELCO Lighting reserves the right to make specification and design changes without notice.