

Project name:		
Fixture type:		
Date:		

6" Airtight IC Remodel Housing




Features

- 6" Airtight IC Remodel Housing for direct contact with ceiling insulation.
- Unit slips through 6 3/8" ceiling cut out.
- Integral flange secures fixture against ceiling.
- Four remodel clips secure housing and accommodate various ceiling thickness.
- Integral thermal protector guards against improper lamping.
- Adjustable socket bracket allows for different lamp types/sizes and proper and consistent lamp positioning.
- Wiring box for use with 75°C supply wire.
- Lamp: PAR
- cUL Listed for damp location and for feed through.

Specifications

Wattage	90W			
Voltage	120V			
Lamp Type	Medium Base (E26)			
Damp Location Listed				

Dimensions



Technical Details

Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- · Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- · Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. Maximum hole cutout is 6 3/8". See installation sheet for detailed information.

Electrical:

- Input Voltage: 120V AC.
- Thermally protected against improper lamping.

Trims: Compatible with ELCO 6" Line Voltage PAR trims.

Lamp: Designed for use with Medium Base (E26) PAR lamps up to 90W.

Listings:

- · cUL Listed for Damp Location.
- · cUL Listed for Feed Through.
- cul Listed for Direct Contact with Insulation and Combustible Material.
- · Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

Product Numbers

Item	Lamp type	Watts	Voltage
EL7RICA	Medium Base (E26)	90W	120V