

# 6" Cedar System New Construction Housing w/Driver

Non-IC Airtight housing for residential and light commercial, 850 to 2000 lumens.



## Features

- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- Meets Title 24 requirements.
- Flicker-Free Dimming.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 6" LED Light Engines.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

## Specifications

<b>Lumens</b>	2000 lm
<b>Voltage</b>	120/277V
<b>Dimmable</b>	Triac/ELV/0-10V
<b>Power Factor</b>	≥0.95
<b>Damp Location</b>	Listed

## Options



**Optional Butterfly Bracket**

## Technical Details

### Construction:

- Non-IC Frame for non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.

### Installation:

- Designed for ceiling plenums where 2x8 joists or taller are used.
- High strength hanger bars can easily be nailed to joists.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

**Hanger Bars:** Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

### Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.95.



**Emergency Battery Pack:** Optional 90 minute battery pack available with test indicator switch. Note that double wall housings require Access From Above Ceiling for Battery Maintenance.

### Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 51% with a compatible dimmer.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.

**Listings:** cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Feed Through.

## Dimensions



## Product Number

Item	Lumens	Voltage	Dimming
<b>E6LC20D2</b>	2000 lm	120/277V	Triac/ELV/0-10V

# Product Number Builder

Example: **E6LC082**

ELCO Cedar 6" Housing

Lumens

Dimming

Generation

Optional

**E6LC**

**08** 850 lm

**12** 1250 lm

**16** 1600 lm

**20** 2000 lm

120V Triac/ELV

**D** 120/277V Triac/ELV/0-10V

**SD** Sunset

**L** Lutron

**2** Gen 2

Gen 1

No EM

**EM1** Emer. Backup up to 700 lm

**EM2** Emer. Backup to 1100 lm

# Compatible Products

For use with 6" Cedar™ Non-IC LED housings

## 6" Cedar™ LED Light Engines



**Round Reflector Trim**

**E610C**  
Finishes:  
(W, B, BZ, C, G, H)



**Round Drop Glass Reflector Trim**

**E612C**  
Finishes:  
(W, B, BZ, C, G, H)



**Round Baffle Trim**

**E614C**  
Finishes:  
(W, B, BZ, BB)



**Round Adjustable Baffle Trim**

**E616C**  
Finishes:  
(W, B, BZ)



**Round Adjustable Reflector Trim**

**E617C**  
Finishes:  
(W, B, BZ, C, H)

### PRODUCT NUMBER BUILDER

6" Cedar™ Trim	Style	Lumen	Color Temperature	Finish
<b>E6</b>				
	<b>10C</b> Reflector	<b>08</b> 850 lm (8.76W)	<b>27</b> 2700K	<b>W</b> All White
	<b>12C</b> Drop Glass	<b>12</b> 1250 lm (12.88W)	<b>30</b> 3000K	<b>B</b> Black w/White Ring
	<b>14C</b> Baffle	<b>16</b> 1600 lm (18W)	<b>35</b> 3500K	<b>BZ</b> All Bronze
	<b>16C</b> Adjustable Baffle	<b>20</b> 2000 lm (20.6W)	<b>40</b> 4000K	<b>BB</b> All Black
	<b>17C</b> Adjustable Reflector		<b>50</b> 5000K	<b>C</b> Chrome w/White Ring
			<b>SD</b> Sunset Dimming	<b>G</b> Gold w/White Ring
				<b>H</b> Haze w/White Ring

## 6" Accessories



**Fire Cover**

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



**Fire Enclosure**

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



**Mica Fire Tape**

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L