

# 6" Cedar System New Construction IC Airtight Housing w/Driver

Single Wall IC Airtight housing for high-end residential and light commercial, 850 to 1250 lumens.





## Features

- cUL Listed for direct contact with insulation.
- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- Meets Title 24 requirements.
- Flicker-Free Dimming.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 6" LED Light Engines.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

## Specifications

|                      |           |
|----------------------|-----------|
| <b>Lumens</b>        | 1600 lm   |
| <b>Voltage</b>       | 120V      |
| <b>Dimmable</b>      | Triac/ELV |
| <b>Power Factor</b>  | ≥0.95     |
| <b>Damp Location</b> | Listed    |

## Dimensions



## Technical Details

### Construction:

- Single wall IC rated for direct contact with insulation. For use in IC and non-IC conditions. 850 or 1250 lumens.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

### Installation:

- Designed for ceiling plenums where 2x8 joists or taller are used.
- High strength hanger bars can easily be nailed to joists.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

**Hanger Bars:** Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

### Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.95.

**Emergency Battery Pack:** Optional 90 minute battery pack available with test indicator switch. Note that double wall housings require Access From Above Ceiling for Battery Maintenance.

### Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 5% with a compatible dimmer.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.

**Listings:** cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Direct Contact

## Product Number

| Item              | Lumens  | Voltage | Dimming   |
|-------------------|---------|---------|-----------|
| <b>E6LC16ICA2</b> | 1600 lm | 120V    | Triac/ELV |

## Product Number Builder Example: E6LC08ICA2

| ELCO Cedar 6" Housing | Lumens   | IC Airtight          | Dimming  | Generation              | Optional  |
|-----------------------|--|----------------------|--|-------------------------|---|
| <b>E6LC</b>           | <input type="text"/>                                       | <input type="text"/> | <input type="text"/>   | <input type="text"/>    | <input type="text"/>  |
|                       | <b>08</b> 850 lm<br><b>12</b> 1200 lm<br><b>16</b> 1600 lm | <b>ICA</b> ICA       | 120V Triac/ELV<br><b>D</b> 120/277V Triac/ELV/0-10V<br><b>SD</b> Sunset<br><b>L</b> Lutron | <b>2</b> Gen 2<br>Gen 1 | No EM<br><b>EM1</b> Emer. Backup up to 700 lm<br><b>EM2</b> Emer. Backup to 1100 lm |

# Compatible Products

For use with 6" Cedar™ IC LED housings

## 6" Cedar™ LED Light Engines



**Round Reflector Trim**

**E610C**  
Finishes:  
(W, B, BZ, C, G, H)



**Round Drop Glass Reflector Trim**

**E612C**  
Finishes:  
(W, B, BZ, C, G, H)



**Round Baffle Trim**

**E614C**  
Finishes:  
(W, B, BZ, BB)



**Round Adjustable Baffle Trim**

**E616C**  
Finishes:  
(W, B, BZ)



**Round Adjustable Reflector Trim**

**E617C**  
Finishes:  
(W, B, BZ, C, H)

### PRODUCT NUMBER BUILDER

| 6" Cedar™ Trim | Style                           | Lumen                      | Color Temperature        | Finish                       |
|----------------|---------------------------------|----------------------------|--------------------------|------------------------------|
| <b>E6</b>      |                                 |                            |                          |                              |
|                | <b>10C</b> Reflector            | <b>08</b> 850 lm (8.76W)   | <b>27</b> 2700K          | <b>W</b> All White           |
|                | <b>12C</b> Drop Glass           | <b>12</b> 1250 lm (12.88W) | <b>30</b> 3000K          | <b>B</b> Black w/White Ring  |
|                | <b>14C</b> Baffle               | <b>16</b> 1600 lm (18W)    | <b>35</b> 3500K          | <b>BZ</b> All Bronze         |
|                | <b>16C</b> Adjustable Baffle    |                            | <b>40</b> 4000K          | <b>BB</b> All Black          |
|                | <b>17C</b> Adjustable Reflector |                            | <b>50</b> 5000K          | <b>C</b> Chrome w/White Ring |
|                |                                 |                            | <b>SD</b> Sunset Dimming | <b>G</b> Gold w/White Ring   |
|                |                                 |                            |                          | <b>H</b> Haze w/White Ring   |

## 6" Accessories



**Fire Cover**

| CAT NO. | SPECIFICATIONS      |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |



**Fire Enclosure**

| CAT NO.    | SPECIFICATIONS                |
|------------|-------------------------------|
| FIREENCL   | 20 3/8" L x 14 3/8" W         |
| FIREENCL-S | Shallow,<br>16" L x 14 3/8" W |



**Mica Fire Tape**

| CAT NO.  | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |