

6" Cedar System Remodel Housing w/Driver

Non-IC Airtight remodel housing for residential and light commercial, 850 to 2000 lumens.




Features

- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- Meets Title 24 requirements.
- Flicker-Free Dimming.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 6" LED Light Engines.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Lumens	1250 lm
Voltage	120/277V
Dimmable	Triac/ELV/0-10V
Power Factor	≥0.95
Damp Location	Listed

Dimensions



Technical Details

Construction:

- Non-IC Frame for non-IC conditions.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

Installation:

- Designed for ceiling plenums where 2x8 joists or taller are used.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.95.

Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 5% with a compatible dimmer.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.

Listings: cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Feed Through.

Product Number

Item	Lumens	Voltage	Dimming
E6LRC12D2	1250 lm	120/277V	Triac/ELV/0-10V

Product Number Builder

Example: **E6LRC082**

ELCO Cedar 6" Remodel
Housing

Lumens

Dimming

Generation

Optional

E6LRC

- 08** 850 lm
- 12** 1250 lm
- 16** 1600 lm
- 20** 2000 lm

- 120V Triac/ELV
- D** 120/277V
Triac/ELV/0-10V
- SD** Sunset
- L** Lutron

- 2** Gen 2
- Gen 1

- No EM
- EM1** Emer. Backup up to 700
lm
- EM2** Emer. Backup to 1100
lm

Compatible Products

For use with 6" Cedar™ Non-IC LED housings

6" Cedar™ LED Light Engines



Round Reflector Trim

E610C
Finishes:
(W, B, BZ, C, G, H)



Round Drop Glass Reflector Trim

E612C
Finishes:
(W, B, BZ, C, G, H)



Round Baffle Trim

E614C
Finishes:
(W, B, BZ, BB)



Round Adjustable Baffle Trim

E616C
Finishes:
(W, B, BZ)



Round Adjustable Reflector Trim

E617C
Finishes:
(W, B, BZ, C, H)

PRODUCT NUMBER BUILDER

6" Cedar™ Trim	Style	Lumen	Color Temperature	Finish
E6				
	10C Reflector	08 850 lm (8.76W)	27 2700K	W All White
	12C Drop Glass	12 1250 lm (12.88W)	30 3000K	B Black w/White Ring
	14C Baffle	16 1600 lm (18W)	35 3500K	BZ All Bronze
	16C Adjustable Baffle	20 2000 lm (20.6W)	40 4000K	BB All Black
	17C Adjustable Reflector		50 5000K	C Chrome w/White Ring
			SD Sunset Dimming	G Gold w/White Ring
				H Haze w/White Ring

6" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L