

6" Cedar System Remodel Housing w/Driver

Non-IC Airtight remodel housing for residential and light commercial, 850 to 2000 lumens.




Features

- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- Meets Title 24 requirements.
- Flicker-Free Dimming.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 6" LED Light Engines.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Lumens	850 lm - 2000 lm
Voltage	120/277V or 120V
Dimmable	Triac/ELV, Triac/ELV/0-10V, Sunset
Power Factor	≥0.95
Damp Location Listed	

Dimensions



Technical Details

Construction:

- Non-IC Frame for non-IC conditions.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

Installation:

- Designed for ceiling plenums where 2x8 joists or taller are used.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.95.

Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 5% with a compatible dimmer.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.

Listings: cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Feed Through.

Product Numbers

Item	Lumens	Voltage	Dimming
E6LRC082	850 lm	120V	Triac/ELV
E6LRC08D2	850 lm	120/277V	Triac/ELV/0-10V
E6LRC08SD	850 lm	120/277V	Sunset
E6LRC122	1250 lm	120V	Triac/ELV
E6LRC12D2	1250 lm	120/277V	Triac/ELV/0-10V
E6LRC12SD	1250 lm	120/277V	Sunset
E6LRC162	1600 lm	120V	Triac/ELV
E6LRC16D2	1600 lm	120/277V	Triac/ELV/0-10V
E6LRC16SD	1600 lm	120/277V	Sunset
E6LRC202	2000 lm	120V	Triac/ELV
E6LRC20D2	2000 lm	120/277V	Triac/ELV/0-10V
E6LRC20SD	2000 lm	120/277V	Sunset

Product Number Builder

Example: E6LRC082

ELCO Cedar 6" Remodel Housing	Lumens	Dimming	Generation	Optional
E6LRC				
	08 850 lm	120V Triac/ELV	2 Gen 2	No EM
	12 1250 lm	D 120/277V	Gen 1	EM1 Emer. Backup up to 700 lm
	16 1600 lm	Triac/ELV/0-10V		EM2 Emer. Backup to 1100 lm
	20 2000 lm	SD Sunset		
		L Lutron		

Compatible Products

For use with 6" Cedar™ Non-IC LED housings



6" Cedar™ LED Light Engines



Round Reflector Trim

E610C

Finishes:

(W, B, BZ, C, G, H)



Round Drop Glass Reflector Trim

E612C

Finishes:

(W, B, BZ, C, G, H)



Round Baffle Trim

E614C

Finishes:

(W, B, BZ, BB)



Round Adjustable Baffle Trim

E616C

Finishes:

(W, B, BZ)



Round Adjustable Reflector Trim

E617C

Finishes:

(W, B, BZ, C, H)

PRODUCT NUMBER BUILDER

6" Cedar™ Trim	Style	Lumen	Color Temperature	Finish
E6				
	10C Reflector	08 850 lm (8.76W)	27 2700K	W All White
	12C Drop Glass	12 1250 lm (12.88W)	30 3000K	B Black w/White Ring
	14C Baffle	16 1600 lm (18W)	35 3500K	BZ All Bronze
	16C Adjustable Baffle	20 2000 lm (20.6W)	40 4000K	BB All Black
	17C Adjustable Reflector		50 5000K	C Chrome w/White Ring
			SD Sunset Dimming	G Gold w/White Ring
				H Haze w/White Ring

6" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L