

Project name:		
Fixture type:		
Date:		

6" Die-cast Round Wall Wash Trim for PAR LAMPS

6" diecast Round Wall Wash Trim. For use with PAR Lamps.



Features

- 6" Round Wall Wash
- Lamp: PAR Lamp.

Technical Details

Construction: Diecast aluminum with a powder-coated finish.

Installation: Torsion springs securely mount trim into the housing and keep ring flush with the ceiling.

Compatible Housing: Compatible with 6" IC and Non-IC housings.

Lamp: PAR Lamp.

Options








White

Bronze

Black

Dimensions



Product Number

Item	Finish
ELL6815BZ	All Bronze

Product Number Builder Example: ELL6815W

6" Round Wall Wash Trim

Finish

ELL6815

W All White

BZ All Bronze

B All Black

Compatible Products



For use with 6" Trims for PAR Lamps

6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL ZICANID	90W without Socket Bracket








6" Airtight IC Housing Remodel



6" Shallow Airtight IC Housing

New Construction



6" Shallow Airtight IC Housing Remodel


CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.

CAT NO.	SPECIFICATIONS	
R10H	Lamp: 150W MAX.	

CAT NO.	SPECIFICATIONS	
PP10H	Lamp: 150W MAX	



6" Shallow Housing New Construction

6	-	
FI	0	00
+ I	. 8	
100	Wan.	V

6" Shallow Housing Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

Compatible Products



For use with 6" Trims for PAR Lamps

6" Accessories







Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow. 16" L x 14 3%'

CAT NO.	SPECIFICATIONS
FIRETAPE	³ / ₄ " W × 16' L