

6" Eyeball Trim



Features

- Eyeball.
- Lamp: 75W MAX R30, 100W MAX PAR30.
- O.D.: 8".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Integral gimbal ring holds lamp and allows for 35° adjustability.
- Diecast trim for durability and lasting quality.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.

Options



White



Black



Bronze

Product Numbers

Item	Finish
EL18W	All White
EL18B	All Black
EL18BZ	All Bronze

Product Number Builder Example: EL18W

6" Eyeball Trim

Finish

EL18

W	All White
B	All Black
BZ	All Bronze

Compatible Products

For use with 6" Trims for PAR Lamps

6" Line Voltage ICA Housings



6" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket



6" Airtight IC Housing
Double Wall New Construction

CAT NO.	SPECIFICATIONS
EL7IC100A	Lamp: 100W MAX.



6" Airtight IC 2-Hour Fire Rated Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7FICA	90W



6" Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.



6" Shallow Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.



6" Shallow Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.



6" Airtight IC Universal Housing
New Construction

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.



6" Airtight IC Universal Housing
Remodel

CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.



6" Shallow Housing
New Construction

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)



6" Shallow Housing
Remodel

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

Compatible Products

For use with 6" Trims for PAR Lamps



6" Accessories



Fire Cover



Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L