

6" LED Light Engine with Baffle Trim

The perfect lighting solution for high-end residential and light commercial projects.



Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

| | |
|---------------------|---------|
| Wattage | 18W |
| Lumens | 1600 lm |
| Color Temp. | 3500K |
| Lamp Type | LED |
| Beam Angle | 60° |
| CRI | 93+ |
| Wet Location | Listed |

Options



All White

Black w/White ring

All Bronze

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Installation: Must be installed on a Cedar™ System frame with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.


LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant. California Title 24 (JA8-2016-E).

Dimensions



Product Number Builder Example: E614C0827W2

| ELCO 6" Baffle | Lumens | Color Temp. | Finish | Generation | Beam Angle |
|----------------|-------------------|-------------------------------|--------------------------------|----------------|--------------------|
| E614C | | | | | |
| | 08 850 lm | 27 2700K | W All White | 2 Gen 2 | 60° lens |
| | 12 1250 lm | 30 3000K | B Black with White Trim | 1 Gen 1 | -F 38° lens |
| | 16 1600 lm | 35 3500K | BZ All Bronze | | -N 24° lens |
| | 20 2000 lm | 40 4000K | BB All Black | | -S 15° lens |
| | | 50 5000K | | | |
| | | SD Sunset ¹ | | | |


¹ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

LED Light Engine

Multiplier: 2700K (x 0.88), 3000K (x 0.92), 3500K (x 0.96)

PHOTOMETRIC REPORT

Product #: E614C2040
 Wattage/Lumens: 21.6W/ 1873 Lm
 Luminaire LPW: 87 Lm/W



CANDLE POWER SUMMARY

| Degrees Vertical | Candle Power |
|------------------|--------------|
| 0 | 2356 |
| 5 | 2304 |
| 15 | 1867 |
| 25 | 1498 |
| 35 | 638 |
| 45 | 58 |
| 55 | 2 |
| 65 | 1 |
| 75 | 0 |
| 85 | 0 |
| 90 | 0 |

ILLUMINANCE AT A DISTANCE

| Distance to Target Plane | Footcandles Beam Center | Beam Diameter |
|--------------------------|-------------------------|---------------|
| 4' | 147 | 4.5' |
| 6' | 65.4 | 6.8' |
| 8' | 36.8 | 9.1' |
| 10' | 23.6 | 11.3' |

ZONAL LUMEN SUMMARY

| Zone | Lumens | % Luminaire |
|-------|---------|-------------|
| 0-30° | 1404.49 | 75.00 |
| 0-40° | 1806.64 | 96.50 |
| 0-60° | 1871.47 | 99.90 |
| 0-90° | 1872.88 | 100.00 |

Compatible Products

For use with 6" Cedar™ Light Engines

6" Cedar™ Dedicated LED ICA Housings



2-Hour Fire Rated
6" ICA Housing
New Construction



6" ICA Housing
New Construction



6" ICA Housing
New Construction




6" ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS |
|---------|----------------|---------|----------------|---------|----------------|---------|----------------|
| E6FH | Up to 1250lm | E6LC | Up to 2000lm | E6LC | Up to 1250lm | E6LRC | Up to 1250lm |

6" Cedar™ Dedicated LED Non-IC Housings



6" Non-IC Housing
New Construction



6" Non-IC Housing
Remodel

| CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS |
|---------|----------------|---------|----------------|
| E6LC | Up to 2000lm | E6LRC | Up to 2000lm |

PRODUCT NUMBER BUILDER

| Housing Type | Lumen | ICA Airtight | Dimming | Optional |
|------------------------------|----------------------|------------------------|-----------------------------------|--|
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| E6FH Fire Rated | 08 850 lm | (Blank) Non-IC | (Blank) 120V Triac/ELV | EM1 Emergency Backup up to 700 lm output |
| E6LC New Construction | 12 1250 lm | ICA IC Airtight | D 120/277V Triac/ELV/0-10V | EM2 Emergency Backup up to 1100 lm output |
| E6LRC Remodel | 16 1600 lm | | L Lutron | |
| | 20 2000 lm | | | |