

6" LED Light Engine with Reflector Trim

The perfect lighting solution for high-end residential and light commercial projects.



Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2.
Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	8.76W
Lumens	850 lm
Color Temp.	5000K
Lamp Type	LED
Beam Angle	60°
CRI	93+
Wet Location	Listed

Options



All White



Haze w/White Trim



Chrome w/White Trim



All Bronze



Black w/White Trim

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Installation: Must be installed on a Cedar™ System frame with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.


LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant. California Title 24 (JA8-2016-E).

Dimensions



Product Number Builder Example: E610C0827W2

ELCO 6" Reflector	Lumens	Color Temp.	Finish	Generation	Beam Angle			
E610C								
08	850 lm	27	2700K	W	All White	2	Gen 2	60º lens
12	1250 lm	30	3000K	BZ	All Bronze	1	Gen 1	-F 38º lens
16	1600 lm	35	3500K	B	Black with White Trim			-N 24º lens
20	2000 lm	40	4000K	C	Chrome with White Trim			-S 15º lens
		50	5000K					
		SD	Sunset ¹	H	Haze with White Trim			


¹ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

LED Light Engine

Multiplier: 2700K (x 0.96), 3000K (x 1.04), 3500K (x 1.08), 4000K (x 1.12)

PHOTOMETRIC REPORT

Product #: E610C1230
Wattage/Lumens: 12.7W/ 1134 Lm
Luminaire LPW: 89 Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	1807
5	1701
15	1159
25	911
35	339
45	25
55	1
65	1
75	0
85	0
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	113	3.8'
6'	50.2	5.6'
8'	28.2	7.5'
10'	18.1	9.4'

ZONAL LUMEN SUMMARY


Zone	Lumens	% Luminaire
0-30°	885.02	78.00
0-40°	1104.89	97.40
0-60°	1133.43	99.90
0-90°	1134.36	100.00

LED Light Engine

Multiplier: 3000K (x 1.04), 3500K (x 1.08), 4000K (x 1.12)

PHOTOMETRIC REPORT

Product #: E610C2027
Wattage/Lumens: 21.6W/ 1900 Lm
Luminaire LPW: 88 Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	2390
5	2338
15	1894
25	1519
35	648
45	59
55	2
65	1
75	0
85	0
90	0

ILLUMINANCE AT A DISTANCE



Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	149	4.5'
6'	66.4	6.8'
8'	37.3	9.1'
10'	23.9	11.3'

ZONAL LUMEN SUMMARY



Zone	Lumens	% Luminaire
0-30°	1424.84	75.00
0-40°	1832.83	96.50
0-60°	1898.59	99.90
0-90°	1900.02	100.00

For use with 6" Cedar™ Light Engines

6" Cedar™ Dedicated LED ICA Housings

			
2-Hour Fire Rated 6" ICA Housing New Construction	6" ICA Housing New Construction	6" ICA Housing New Construction	6" ICA Housing Remodel
CAT NO. SPECIFICATIONS	CAT NO. SPECIFICATIONS	CAT NO. SPECIFICATIONS	CAT NO. SPECIFICATIONS
E6FH Up to 1250lm	E6LC Up to 2000lm	E6LC Up to 1250lm	E6LRC Up to 1250lm

6" Cedar™ Dedicated LED Non-IC Housings

	
6" Non-IC Housing New Construction	6" Non-IC Housing Remodel
CAT NO. SPECIFICATIONS	CAT NO. SPECIFICATIONS
E6LC Up to 2000lm	E6LRC Up to 2000lm

PRODUCT NUMBER BUILDER				
Housing Type	Lumen	ICA Airtight	Dimming	Optional
E6FH Fire Rated	08 850 lm	(Blank) Non-IC	(Blank) 120V Triac/ELV	EM1 Emergency Backup up to 700 lm output
E6LC New Construction	12 1250 lm	ICA IC Airtight	D 120/277V Triac/ELV/0-10V	EM2 Emergency Backup up to 1100 lm output
E6LRC Remodel	16 1600 lm		L Lutron	
	20 2000 lm			