

6" LED Light Engine with Wall Wash Trim (850-6000 Im)



Features

- Dimmable Triac/ELV or 0-10V.
- USA Designed and Assembled.
- Frame sold separately (see Compatible Housings).
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

| | |
|---------------------|---------|
| Wattage | 12.8W |
| Lumens | 1250 lm |
| Color Temp. | 3000K |
| Lamp Type | LED |
| Beam Angle | 60° |
| CRI | 93+ |
| Wet Location | Listed |

Options



Black



Chrome



All Haze(semi-specular)



Haze w/White Trim



White

Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED technology.

Reflector Construction: Reflector is one piece, deep, self-flanged construction spun from .05" thick High Grade Aluminum. Reflector allows for minimal glare and a strong glare cut-off. Wall wash reflector pushes light in one direction to evenly light up a wall or frame.

Installation: Must be installed on a Laurel System frame with compatible lumen rating. Frames are available for New Construction, Remodel and as a Retrofit Kit.


LED Technology:

- Extremely accurate Color Rendering Index of 93+ CRI.
- Efficacy of >90 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.


Listings: cULus Listed for Wet Location. RoHS Compliant.

850 Im - 3000 Im Series



Warranty: ELCO Products are built to last. 5-year Limited warranty.

4000 lm - 6000 lm Series



Product Number Builder Example: E611L0827W2

| ELCO 6" Wall Wash | Laurel | Lumens | Color Temp. | Finish | Generation | Beam Angle |
|-------------------|----------|-------------------|---------------------------------|-----------------------------------|----------------|----------------------------|
| E611 | L | | | | | |
| | | 08 850 lm | 27 2700K ¹ | W All White | 2 Gen 2 | 60° |
| | | 12 1250 lm | 30 3000K | B All Black | 1 Gen 1 | -F 38° ¹ |
| | | 16 1600 lm | 35 3500K | C All Chrome | | -N 24° ¹ |
| | | 20 2000 lm | 40 4000K | H All Haze (Semi-Specular) | | -S 15° ¹ |
| | | 30 3000 lm | 50 5000K | HW Haze with White Trim | | |
| | | 40 4000 lm | SD Sunset ^{1,2} | | | |
| | | 60 6000 lm | | | | |

¹ Available for lumen packages up to 3000 lm only

² Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

Compatible Products




For use with 6" Laurel™ Light Engines

6" Laurel™ Commercial LED Frames



6" Architectural Frame
E6LH



6" Plaster Frame
E6LF



6" Remodel Frame
E6LR



6" Retrofit Kit
E6LT

PRODUCT NUMBER BUILDER

| Frame Type | Voltage | Lumen | Dimming | Optional | Generation |
|---------------------------|----------------------|----------------------|--------------------------|--|----------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| E6LH Architectural | U 120/277V | 08 850 lm | D Triac/ELV/0-10V | EM1 Emergency Backup up to 700 lm output | (blank) Gen 1 |
| E6LF Plaster | | 12 1250 lm | S Sunset | EM2 Emergency Backup up to 1100 lm output | 2 Gen 2 |
| E6LR Remodel | | 16 1600 lm | L Lutron | | |
| E6LT Retrofit | | 20 2000 lm | | | |
| | | 30 3000 lm | | | |
| | | 40 4000 lm | | | |
| | | 60 6000 lm | | | |