

Project name:		
Fixture type:		
Date:		

# **6" One Piece Self Flanged Baffle Trim with Clips**



#### **Features**

- Baffle, self-flanged.
- Lamp: 75W MAX PAR30 or R30, 90W MAX PAR38, 120W MAX BR40.
- O.D.: 7 1/4".

#### **Technical Details**

#### Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated LED Housings.

Lamp: Compatible with Medium base (E26) PAR type.

#### **Product Numbers**

Item	Finish
ELM303W	All White

## **Compatible** Products



For use with 6" Trims for PAR Lamps

### 6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket



CAT NO. SPECIFICATIONS
EL7FICA 90W



6" Airtight IC Housing Remodel



6" Shallow Airtight IC Housing

New Construction

6	-	
6	-	100
F F	. 1	
100	400	0 -

6" Shallow Airtight IC Housing Remodel

CAI NO.	SPECIFICATIONS	
EL7RICA	Lamp: 90W MAX.	

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS	
RR9ICA	Lamp: 75W MAX.	



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel


CAT NO.	SPECIFICATIONS	
EL7ICA-G24	Lamp: 27W MAX.	

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.

CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.



6" Shallow Housing New Construction



6" Shallow Housing Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (F26)

# **Compatible** Products



For use with 6" Trims for PAR Lamps

### 6" Accessories







-	ire	-r	10	$\sim$	ure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H × 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3%

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W × 16' L