

# 6" Open Trim with Coil Springs



## Features

- Open Trim.
- Lamp: 75W MAX PAR30 or R30.
- O.D.: 8".

## Technical Details

**Construction:** Meticulously manufactured trim with a powder coated or anodized finish.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 6" Integrated Line Voltage Housings.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Product Number

Item	Finish
EL30W	All White

## Product Number Builder Example: EL30W

6" Open Trim

EL30

Finish

**W** All White

# Compatible Products

For use with 6" Trims for PAR Lamps

## 6" Line Voltage ICA Housings



6" Airtight IC Housing  
**New Construction**



6" Airtight IC Housing  
**Double Wall New Construction**



6" Airtight IC 2-Hour Fire Rated Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket

CAT NO.	SPECIFICATIONS
EL7IC100A	Lamp: 100W MAX.


CAT NO.	SPECIFICATIONS
EL7FICA	90W



6" Airtight IC Housing  
**Remodel**



6" Shallow Airtight IC Housing  
**New Construction**



6" Shallow Airtight IC Housing  
**Remodel**


CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket  
**New Construction**



6" Airtight IC Universal Housing  
**New Construction**



6" Airtight IC Universal Housing  
**Remodel**


CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.

CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.



6" Shallow Housing  
**New Construction**



6" Shallow Housing  
**Remodel**

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

# Compatible Products

For use with 6" Trims for PAR Lamps

## 6" Accessories

---



Fire Cover



Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L