

6" Pex™ Round Adjustable Pinhole with Reflector Trim for Koto Module



Pex™ 6" diecast Round Adjustable Pinhole Reflector Trim. One-piece trims with twist-on system for easy tool-free installation. For use with Koto LED Module.

Features

- 6" Round Reflector
- Convenient twist-on design for ease of installation
- 25° tilt
- Lamp: Koto LED Module
- O.D.: 8"
- Pinhole Diameter: 1 3/4"

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-on design allows for easy mounting onto the Koto™ LED Module. Torsion springs securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Koto Housings.

Lamp: Koto™ LED Module


Options



All White

Black w/White Trim Haze w/White Trim

Dimensions



Product Number

| Item | Finish |
|----------|-----------|
| ELK6427W | All White |

Product Number Builder Example: ELK6427W

6" Pex™ Round Reflector Trim for Koto Module

Finish


ELK6427

| | |
|--------------------------------|--|
| W All White | |
| B Black with White Trim | |
| H Haze with White Trim | |

Compatible Products

For use with 6" Koto™ Twist-On Trims

Koto™ LED Module



Koto™ LED Module
ELK07, ELK09, & ELK11

| PRODUCT NUMBER BUILDER | | | | | |
|------------------------|---------|---------------------------------------|---------------------------------------|--|--|
| Koto™ LED Module | Lumens | Color Temperature | Beam Angle | | |
| ELK | | | | | |
| 07 | 750 lm | 27 2700K | (blank) 38° lens (Standard) | | |
| 09 | 950 lm | 30 3000K | -S 18° lens | | |
| 11 | 1150 lm | 35 3500K | -N 25° lens | | |
| | | 40 4000K | -W 60° lens | | |
| | | SD Sunset Dimming (For ELK09 & ELK11) | -FC 18° - 50° Adjustable (ELK07 Only) | | |

ACCESSORIES




Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens
*EP732C, EP733C, EP734C
 Included with standard module



Snout


L50W White
L50B Black



Secondary Optics

L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter
L57 White Hex Louver
L52 Blue Lens
L53 Pink Shifter

*Standard module includes 38° installed with 25° & 60° field changeable lenses.




Koto™ LED Module with 5-CCT Switch



Product Number

ELK08CT5 825 lm, 5-CCT, 120V
ELK10CT5 1000 lm, 5-CCT, 120V




12V AC Retrofit Koto™ LED Module

For retrofitting 4" Bi-Pin 12V AC GU5.3 Housings

Product Number

ELK0827-12 800 lm, 2700K, 12V AC
ELK0830-12 800 lm, 3000K, 12V AC
ELK08SD-12 800 lm, Sunset, 12V AC

6" Koto™ Dedicated LED ICA Housings



6" Standard ICA Housing
New Construction



6" Standard Remodel ICA Housing
Remodel



6" 2-Hour Fire Rated ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|----------------------|
| EL770ICA | 7" Height |
| EL760ICA | 5 ½" Height, Shallow |

| CAT NO. | SPECIFICATIONS |
|-----------|----------------------|
| EL770RICA | 7 ½" Height |
| EL760RICA | 5 ½" Height, Shallow |


| CAT NO. | SPECIFICATIONS |
|-----------|---------------------------|
| EL76FICA | 7 ¾" Height - Sound Rated |
| EL75FICAS | 6 ¾" Height, Shallow |

Compatible Products



For use with 6" Koto™ Twist-On Trims

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

| PRODUCT NUMBER BUILDER | | | |
|------------------------|----------------|--------------------------------|---------------------------------------|
| Koto™ LED Light Engine | Lumens | Color Temperature | Beam Angle |
| ELK | | | |
| 19 | 750 - 850 lm | 27D 2700K | (blank) 38° lens (Standard) |
| 21 | 1100 - 1500 lm | 30D 3000K | -S 18° lens |
| | | 35D 3500K | -N 25° lens |
| | | 40D 4000K | -W 60° lens |
| | | SD Sunset Dimming (ELK19 Only) | -FC 18° - 50° Adjustable (ELK21 Only) |

*Standard module includes 38° installed with 25° & 60° field changeable lenses.

ACCESSORIES



Lens

| | |
|--|----------|
| EP731C | 18° Lens |
| EP732C | 25° Lens |
| EP733C | 38° Lens |
| EP734C | 60° Lens |
| <small>*EP732C, EP733C, EP734C Included with standard module</small> | |



Snoot

| | |
|-------------|-------|
| L50W | White |
| L50B | Black |



Secondary Optics

| | | | |
|------------|---------------|------------|------------------|
| L45 | Hex Louver | L57 | White Hex Louver |
| L46 | Linear Lens | L52 | Blue Lens |
| L47 | Spread Louver | L53 | Pink Shifter |
| L49 | Frosted Lens | | |
| L51 | Color Shifter | | |

6" Koto™ Dedicated LED ICA Housing



6" Koto™ Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|--|
| E6LK37ICA | 7 ½" Height, Triac/ELV, 120V |
| E6LK38ICAD | 7 ½" Height, 0-10V/Triac/ELV, 120/277V |



6" Maximum Adjustability High Lumen ICA Housing
Use with ELK21 Series Module
Not for use with ELK19 Series Module
Double Wall

| CAT NO. | SPECIFICATIONS |
|------------|---|
| E6LK43ICA | 7 ¼" Height, 120V, Triac/ELV, 1250 lm |
| E6LK44ICAD | 7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1250 lm |
| E6LK56ICA | 7 ¼" Height, 120V, Triac/ELV, 1500 lm |
| E6LK57ICAD | 7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1500 lm |