

6" Pex™ Square Adjustable Reflector for Koto Module

6" Pex™ Square Adjustable Reflector Trim. One-piece diecast trims with twist-on system for easy tool-free installation. For use with Koto LED Module.



Features

- 6" Square Adjustable Reflector
- Convenient twist-lock design for ease of installation
- Lamp: Koto LED Module

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module. Torsion springs securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Koto Housings.


Lamp: Koto™ LED Module

Options



All White All Black Haze w/White Trim

Dimensions



Product Numbers

| Item | Description | Finish |
|-----------|-----------------------------|----------------------|
| ELK6829W | Square Adjustable Reflector | All White |
| ELK6829BB | Square Adjustable Reflector | All Black |
| ELK6829H | Square Adjustable Reflector | Haze with White Trim |

Product Number Builder

Example: ELK6829W

6" Pex™ Square Adj. Reflector Trim for Koto Module

Finish

ELK6829


- W** All White
- BB** All Black
- H** Haze with White Trim

Compatible Products

For use with 6" Koto™ Twist-On Trims



Koto™ LED Module



Koto™ LED Module
ELK07, ELK09, & ELK11

PRODUCT NUMBER BUILDER

| Koto™ LED Module | Lumens | Color Temperature | Beam Angle |
|------------------|---------|---------------------------------------|---------------------------------------|
| ELK | | | |
| 07 | 750 lm | 27 2700K | (blank) 38° lens (Standard) |
| 09 | 950 lm | 30 3000K | -S 18° lens |
| 11 | 1150 lm | 35 3500K | -N 25° lens |
| | | 40 4000K | -W 60° lens |
| | | SD Sunset Dimming (For ELK09 & ELK11) | -FC 18° - 50° Adjustable (ELK07 Only) |

ACCESSORIES



Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens
*EP732C, EP733C, EP734C
Included with standard module

Snout


L50W White
L50B Black



Secondary Optics

L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter
L57 White Hex Louver
L52 Blue Lens
L53 Pink Shifter

*Standard module includes 38° installed with 25° & 60° field changeable lenses.




Koto™ LED Module with 5-CCT Switch



Product Number

ELK08CT5 825 lm, 5-CCT, 120V
ELK10CT5 1000 lm, 5-CCT, 120V




12V AC Retrofit Koto™ LED Module

For retrofitting 4" Bi-Pin 12V AC GU5.3 Housings

Product Number


ELK0827-12 800 lm, 2700K, 12V AC
ELK0830-12 800 lm, 3000K, 12V AC
ELK08SD-12 800 lm, Sunset, 12V AC

6" Koto™ Dedicated LED ICA Housings



6" Standard ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|----------------------|
| EL770ICA | 7" Height |
| EL760ICA | 5 ½" Height, Shallow |



6" Standard Remodel ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-----------|----------------------|
| EL770RICA | 7 ½" Height |
| EL760RICA | 5 ½" Height, Shallow |



6" 2-Hour Fire Rated ICA Housing
New Construction


| CAT NO. | SPECIFICATIONS |
|-----------|---------------------------|
| EL76FICA | 7 ¾" Height - Sound Rated |
| EL75FICAS | 6 ¾" Height, Shallow |

Compatible Products

For use with 6" Koto™ Twist-On Trims



Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

| PRODUCT NUMBER BUILDER | | | |
|------------------------|----------------|--------------------------------|---------------------------------------|
| Koto™ LED Light Engine | Lumens | Color Temperature | Beam Angle |
| ELK | | | |
| 19 | 750 - 850 lm | 27D 2700K | (blank) 38° lens (Standard) |
| 21 | 1100 - 1500 lm | 30D 3000K | -S 18° lens |
| | | 35D 3500K | -N 25° lens |
| | | 40D 4000K | -W 60° lens |
| | | SD Sunset Dimming (ELK19 Only) | -FC 18° - 50° Adjustable (ELK21 Only) |

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

ACCESSORIES



Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens
*EP732C, EP733C, EP734C
Included with standard module



Snoot


L50W White
L50B Black



Secondary Optics

L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter
L57 White Hex Louver
L52 Blue Lens
L53 Pink Shifter

6" Koto™ Dedicated LED ICA Housings



6" Koto™ Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|--|
| E6LK37ICA | 7 ½" Height, Triac/ELV, 120V |
| E6LK38ICAD | 7 ½" Height, 0-10V/Triac/ELV, 120/277V |



6" Maximum Adjustability High Lumen ICA Housing
Use with ELK21 Series Module
Not for use with ELK19 Series Module
Double Wall


| CAT NO. | SPECIFICATIONS |
|------------|---|
| E6LK43ICA | 7 ¼" Height, 120V, Triac/ELV, 1250 lm |
| E6LK44ICAD | 7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1250 lm |
| E6LK56ICA | 7 ¼" Height, 120V, Triac/ELV, 1500 lm |
| E6LK57ICAD | 7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1500 lm |

Compatible Products

For use with 6" Koto™ Twist-On Trims



Koto™ 24V DC LED Light Engine



24V DC Koto™ LED
Light Engine

PRODUCT NUMBER BUILDER

| Koto™ LED Light Engine | Lumens | Color Temperature | Voltage |
|---------------------------|-----------|----------------------|------------|
| ELK | | | |
| | 08 800 lm | 27 2700K | -24 24V DC |
| | | 30 3000K | |

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

ACCESSORIES



Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens

**EP732C, EP733C, EP734C
Included with standard module*



Snoot

L50W White
L50B Black



Secondary Optics


L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter
L57 White Hex Louver
L52 Blue Lens
L53 Pink Shifter

6" Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 2-Hour Fire Rated 6" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|--|
| E24V76FICA | 7 3/4" Height <i>*Requires 24V DC Transformer</i> |




24V DC 6" Standard ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|---|
| E24V770ICA | 7 1/2" Height |
| E24V770ICA-EM5 | Battery Backup, 24W MAX. <i>*Requires 24V DC Transformer</i> |




24V DC 6" Standard ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|--|
| E24V770RICA | 7 1/2" Height <i>*Requires 24V DC Transformer</i> |



24V DC 2-Hour Shallow Fire Rated 6" ICA
New Construction Housing

| CAT NO. | SPECIFICATIONS |
|-------------|---|
| E24V75FICAS | 6 3/16" Height <i>*Requires 24V DC Transformer</i> |



24V DC 6" Shallow ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|---|
| E24V760ICA | 5 1/2" Height |
| E24V760ICA-EM5 | Battery Backup, 24W MAX. <i>*Requires 24V DC Transformer</i> |



24V DC 6" Shallow ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|--|
| E24V760RICA | 5 1/2" Height <i>*Requires 24V DC Transformer</i> |