

6" Round Adjustable Baffle Trim with LED Module & Driver

The perfect lighting solution for high-end residential projects with existing housings.



Features

- Module includes LED Module Driver.
- Triac/ELV dimming.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.

Specifications

Wattage	10.5W - 15.7W
Lumens	850 lm - 1250 lm
Voltage	120V
Color Temp.	2700K - SunsetK
Dimmable	Triac/ELV
Lamp Type	LED
Beam Angle	60° - 60°
CRI	93+
Wet Location	Listed

Options



All White

Black w/White ring

All Bronze

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Compatible Housings: EL76FICA, EL770ICA, EL770RICA.


LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixelation.

Listings:

- UL Listed for Wet Location.
- RoHS Compliant.
- ENERGY STAR® Certified.
- California Title 24 (JA8-2016-E).

Dimensions



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle
E616R0827W, E616R0827B, E616R0827BZ	LED	850 lm	2700K	10.5W	120V	Triac/ELV	60°
E616R1227W, E616R1227B, E616R1227BZ	LED	1250 lm	2700K	15.7W	120V	Triac/ELV	60°
E616R0830W, E616R0830B, E616R0830BZ	LED	850 lm	3000K	10.5W	120V	Triac/ELV	60°
E616R1230W, E616R1230B, E616R1230BZ	LED	1250 lm	3000K	15.7W	120V	Triac/ELV	60°
E616R0835W, E616R0835B, E616R0835BZ	LED	850 lm	3500K	10.5W	120V	Triac/ELV	60°
E616R1235W, E616R1235B, E616R1235BZ	LED	1250 lm	3500K	15.7W	120V	Triac/ELV	60°

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle
E616R0840W, E616R0840B, E616R0840BZ	LED	850 lm	4000K	10.5W	120V	Triac/ELV	60°
E616R1240W, E616R1240B, E616R1240BZ	LED	1250 lm	4000K	15.7W	120V	Triac/ELV	60°
E616R0850W, E616R0850B, E616R0850BZ	LED	850 lm	5000K	10.5W	120V	Triac/ELV	60°
E616R1250W, E616R1250B, E616R1250BZ	LED	1250 lm	5000K	15.7W	120V	Triac/ELV	60°
E616R085DW, E616R085DB, E616R085DBZ	LED	850 lm	SunsetK	10.5W	120V	Triac/ELV	60°
E616R125DW, E616R125DB, E616R125DBZ	LED	1250 lm	SunsetK	15.7W	120V	Triac/ELV	60°

Product Number Builder

Example: **E616R0827W**, **E616R0827B**, **E616R0827BZ**

ELCO 6" Round Adjustable Baffle

E616R

Lumens

08 850 lm
12 1250 lm

Color Temp.

27 2700K
30 3000K
35 3500K
40 4000K
50 5000K
SD Sunset

Finish

W All White
B Black w/White Ring
BZ All Bronze