

# 6" Round LED Adjustable Phenolic Baffle with PAR38 Gimbal Insert

ELCO Lighting's inserts are engineered with energy-efficient LED technology that produces even illumination with an incredible 93+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings manufactured by ELCO or others.



## Features

- Fits ELCO 6" Dedicated LED Recessed Housings, Regular and Shallow.
- Energy Star Certified.
- Title 24 JA8-2019 Compliant.
- Life Span of 50,000 hours L70.
- Includes Medium Base Adapter PSA30.

## Specifications

|             |           |
|-------------|-----------|
| Wattage     | 18W       |
| Lumens      | 1200 lm   |
| Voltage     | 120V      |
| Color Temp. | 2700K     |
| Dimmable    | Triac/ELV |
| Lamp Type   | LED       |
| CRI         | 93+       |

## Options



White



Bronze



Black with White Ring

## Technical Details

**Construction:** For use in IC and non-IC housings. Spun Aluminum for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

**Installation:** Quick connect for use with ELCO housings EL770ICA, EL770RICA, EL76FICA, EL760ICA, EL760RICA.


**Dimmability:** Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.

### Listings:

- RoHS Compliant.
- ENERGY STAR® Certified.
- Title 24 JA8-2019 Compliant.

**Warranty:** ELCO Products are built to last with a 5-year Limited Warranty.

## Dimensions



## Product Number

| Item      | Lamp type | Lumens  | CCT   | Watts | Voltage | Dimming   | Finish     |
|-----------|-----------|---------|-------|-------|---------|-----------|------------|
| EL47627BZ | LED       | 1200 lm | 2700K | 18W   | 120V    | Triac/ELV | All Bronze |

## Product Number Builder

Example: **EL47627BZ**

ELCO 6" LED Insert

Color Temp.

Finish

EL476

27 2700K

30 3000K

W All White

B Black with White Ring


BZ All Bronze

# Compatible Products

For use with 6" LED inserts




## 6" Dedicated LED ICA Housings



6" IC Housing  
New Construction

| CAT NO.    | SPECIFICATIONS |
|------------|----------------|
| EL770ICA   | 24W MAX.       |
| EL770ICA-7 | 24W MAX. 277V  |



6" ICA Housing  
Remodel

| CAT NO.   | SPECIFICATIONS |
|-----------|----------------|
| EL770RICA | 24W MAX.       |




2-Hour Fire Rated 6" ICA Housing  
New Construction

| CAT NO.    | SPECIFICATIONS      |
|------------|---------------------|
| EL76FICA   | 22W - 7 3/4" Height |
| EL76FICA-7 | 22W - 277V          |



6" Shallow IC Housing  
New Construction

| CAT NO.    | SPECIFICATIONS |
|------------|----------------|
| EL760ICA   | 17W MAX.       |
| EL760ICA-7 | 17W MAX. 277V  |



6" Shallow ICA Housing  
Remodel


| CAT NO.   | SPECIFICATIONS |
|-----------|----------------|
| EL760RICA | 17W MAX.       |



2-Hour Fire Rated  
6" Shallow ICA Housing  
New Construction

| CAT NO.   | SPECIFICATIONS                       |
|-----------|--------------------------------------|
| EL75FICAS | Shallow. 24W MAX.<br>6 3/16" Height. |

## 6" Accessories




Emergency Battery Backup

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| KEM-LD5 | 8W, 120/277V   |



Fire Cover

| CAT NO. | SPECIFICATIONS      |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |



Fire Enclosure

| CAT NO.    | SPECIFICATIONS                |
|------------|-------------------------------|
| FIREENCL   | 20 3/8" L x 14 3/8" W         |
| FIREENCL-S | Shallow,<br>16" L x 14 3/8" W |



Mica Fire Tape

| CAT NO.  | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |