

Project name:
Fixture type:
Date:

## 6" Round LED Adjustable Phenolic Baffle with PAR38 **Gimbal Insert**

ELCO Lighting's inserts are engineered with energy-efficient LED technology that produces even illumination with an incredible 93+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings manufactured by ELCO or others.



#### **Features**

- Fits ELCO 6" Dedicated LED Recessed Housings, Regular and Shallow.
- Energy Star Certified.
- Title 24 JA8-2019 Compliant.
- Life Span of 50,000 hours L70.
- Includes Medium Base Adapter PSA30.

### **Specifications**

Wattage	18W
Lumens	1200 lm
Voltage	120V
Color Temp.	2700K - 3000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	93+

#### **Technical Details**

Construction: For use in IC and non-IC housings. Spun Aluminum for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: Quick connect for use with ELCO housings EL770ICA, EL770RICA, EL76FICA, EL760ICA, EL760RICA.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.

- RoHS Compliant.
- ENERGY STAR® Certified.
- Title 24 JA8-2019 Compliant.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

#### **Options**








White

Bronze

Black with White Ring

#### **Dimensions**



#### **Product Numbers**

Item	Lamp type	Lumens	сст	Watts	Voltage	Dimming	Finish
EL47627BZ	LED	1200 lm	2700K	18W	120V	Triac/ELV	All Bronze
EL47630BZ	LED	1200 lm	3000K	18W	120V	Triac/ELV	All Bronze
EL47627W	LED	1200 lm	2700K	18W	120V	Triac/ELV	All White
EL47630W	LED	1200 lm	3000K	18W	120V	Triac/ELV	All White
EL47627B	LED	1200 lm	2700K	18W	120V	Triac/ELV	Black with White Trim
EL47630B	LED	1200 lm	3000K	18W	120V	Triac/ELV	Black with White Trim

## Product Number Builder Example: EL47627BZ

ELCO 6" LED Insert	Color Temp.		Finish
EL476			
	<b>27</b> 2700K	W	All White
	<b>30</b> 3000K	В	Black with White Ring
		BZ	Z All Bronze

# **Compatible** Products



For use with 6" LED inserts

## 6" Dedicated LED ICA Housings



6" IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL770ICA	24W MAX.
EL770ICA-7	24W MAX. 277V



6" ICA Housing Remodel

CAT NO.	SPECIFICATIONS
EL770RICA	24W MAX.




2-Hour Fire Rated 6" ICA Housing New Construction

CAT NO.	SPECIFICATIONS
EL76FICA	22W - 7 ¾" Height
FL76FICA-7	22W - 277V



6" Shallow IC Housing New Construction

CAT NO.	SPECIFICATIONS
EL760ICA	17W MAX.
EL760ICA-7	17W MAX. 277V



6" Shallow ICA Housing Remodel

CAT NO.	SPECIFICATIONS
EL760RICA	17W MAX.



2-Hour Fire Rated 6" Shallow ICA Housing New Construction

CAT NO.	SPECIFICATIONS
EL75FICAS	Shallow. 24W MAX.
	6 3/16" Height.

### 6" Accessories



**Emergency Battery Backup** 

CAT NO.	SPECIFICATIONS
KEM-LD5	8W. 120/277V



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 %" L x 14 %" W
FIREENCL-S	Shallow,
	16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	<sup>3</sup> / <sub>4</sub> " W × 16' L