

6" Round LED Adjustable Phenolic Reflector with PAR30 Gimbal Insert

ELCO Lighting's inserts are engineered with energy-efficient LED technology that produces even illumination with an incredible 93+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings manufactured by ELCO or others.



Features

- Fits ELCO 6" Dedicated LED Recessed Housings, Regular and Shallow.
- Energy Star Certified.
- Title 24 JA8-2019 Compliant.
- Life Span of 50,000 hours L70.
- Includes Medium Base Adapter PSA30.

Specifications

| | |
|----------------------|--|
| Wattage | 15W |
| Lumens | 1050 lm |
| Voltage | 120V |
| Color Temp. | 2700K, 3000K, 3500K, 4000K, 5000K - 3000/2700K, 3000K, 3500K, 4000K, 5000K |
| Dimmable | Triac/ELV |
| Lamp Type | LED |
| CRI | 93+ |
| Damp Location | Listed |

Options



White



Chrome



Black w/White Ring

Technical Details

Construction: For use in IC and non-IC housings. Spun Aluminum for greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.


Installation: Quick connect for use with ELCO housings EL770ICA, EL770RICA, EL76FICA, EL760ICA, EL760RICA.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.

Listings: RoHS Compliant. ENERGY STAR® Certified. Title 24 JA8-2019 Compliant.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Dimensions



Product Numbers

| Item | Lamp type | Lumens | CCT | Watts | Voltage | Dimming | Finish |
|-----------|-----------|---------|--|-------|---------|-----------|-----------------------|
| EL377CT5W | LED | 1050 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 15W | 120V | Triac/ELV | All White |
| EL377CT5B | LED | 1050 lm | 3000/2700K, 3000K, 3500K, 4000K, 5000K | 15W | 120V | Triac/ELV | Black with White Ring |
| EL377CT5C | LED | 1050 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 15W | 120V | Triac/ELV | All Chrome |

Product Number Builder Example: **EL377CT5W**

ELCO 6" LED Insert

Color Temp.

Finish

EL377


CT5 2700K - 5000K

W All White
B Black with White Trim
C All Chrome

Compatible Products


For use with 6" LED inserts

6" Dedicated LED ICA Housings



6" IC Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|----------------|
| EL770ICA | 24W MAX. |
| EL770ICA-7 | 24W MAX. 277V |



6" ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-----------|----------------|
| EL770RICA | 24W MAX. |




2-Hour Fire Rated 6" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|---------------------|
| EL76FICA | 22W - 7 3/4" Height |
| EL76FICA-7 | 22W - 277V |




6" Shallow IC Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|----------------|
| EL760ICA | 17W MAX. |
| EL760ICA-7 | 17W MAX. 277V |



6" Shallow ICA Housing
Remodel


| CAT NO. | SPECIFICATIONS |
|-----------|----------------|
| EL760RICA | 17W MAX. |



2-Hour Fire Rated
6" Shallow ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------------------------|
| EL75FICAS | Shallow. 24W MAX. 6 3/16" Height. |

6" Accessories



Emergency Battery Backup

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| KEM-LD5 | 8W, 120/277V |



Fire Cover

| CAT NO. | SPECIFICATIONS |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |



Fire Enclosure

| CAT NO. | SPECIFICATIONS |
|------------|-------------------------------|
| FIREENCL | 20 3/8" L x 14 3/8" W |
| FIREENCL-S | Shallow, 16" L x 14 3/8" W |



Mica Fire Tape

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |