

6" Shallow Self Flanged Baffle Trim with Torsion Springs



Features

- Shallow Baffle, self-flanged.
- Lamp: 75W MAX PAR30 or R30.
- O.D.: 7 1/4".

Technical Details

Construction:


- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated LED Housings.

Lamp: Compatible with Medium base (E26) PAR type.

Dimensions



Product Numbers


Item	Finish
ELM305W	All White

Compatible Products



For use with 6" Trims for PAR Lamps

6" Line Voltage ICA Housings



6" Airtight IC Housing
New Construction



6" Airtight IC Housing
Double Wall New Construction




6" Airtight IC 2-Hour Fire Rated Housing
New Construction


CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket

CAT NO.	SPECIFICATIONS
EL7IC100A	Lamp: 100W MAX.


CAT NO.	SPECIFICATIONS
EL7FICA	90W



6" Airtight IC Housing
Remodel



6" Shallow Airtight IC Housing
New Construction




6" Shallow Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket
New Construction



6" Airtight IC Universal Housing
New Construction



6" Airtight IC Universal Housing
Remodel


CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.

CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.



6" Shallow Housing
New Construction



6" Shallow Housing
Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

Compatible Products

For use with 6" Trims for PAR Lamps

6" Accessories



Fire Cover



Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L