

Project name:	
Fixture type:	
Date:	

6" Shower Trim with Albalite Lens



Features

- Shower Trim.
- Lamp: 42W MAX. 4 Pin CFL, 60W MAX A19.
- 8" O.D.

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.



Product Number

Item	Finish
EL12KW	All White

Product Number Builder Example: EL12N

6" Shower Trim

Socket Bracket

Finish

REL12

N Nickel

N Nickel

K Socket Bracket

B All Black

W All White

SH White Lexan

BZ All Bronze

CP Copper

Compatible Products



For use with 6" Trims for PAR Lamps

6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL7ICA	90W, with Socket Bracket	
EL7ICANB	90W, without Socket Bracket	



CAT NO. SPECIFICATIONS
EL7FICA 90W



6" Airtight IC Housing Remodel



6" Shallow Airtight IC Housing

New Construction



6" Shallow Airtight IC Housing Remodel


CAT NO.	SPECIFICATIONS	
EL7RICA	Lamp: 90W MAX.	

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

CAT NO.	SPECIFICATIONS	
EL7ICA-G24	Lamp: 27W MAX.	

CAT NO.	SPECIFICATIONS	
R10H	Lamp: 150W MAX.	

CAT NO.	SPECIFICATIONS	
PP10H	Lamp: 150W MAX	



6" Shallow Housing New Construction

6	1	
F	0	00
r }	. 8	
Ans	30	

6" Shallow Housing Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS	
RR9H	Lamp: 75W MAX., Medium Base (F26)	

Compatible Products



For use with 6" Trims for PAR Lamps

6" Accessories







HII	Θ.	⊢n	C	OS	ure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 %" L x 14 %" W
FIREENCL-S	Shallow, 16" L x 14 %" W

CAT NO.	SPECIFICATIONS
FIRETAPE	³ / ₄ " W × 16' L