

Project name:
Fixture type:
Date:

6" Shower Trim with Drop Opal Lens



F	 +ı	ıre	20

- Shower Trim.
- Lamp: (1) 42W max CFL, (2) 13W Quad, 60W MAX A19.
- 0.D.: 8"

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.

Product Numbers

Item	Finish
EL16W	All White

Product Number Builder Example: EL16W

6" Shower Trim	Socket Bracket	Finish
EL16		
	no Socket Bracket	W All White

K Socket Bracket

Compatible Products



For use with 6" Trims for PAR Lamps

6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL7ICA	90W, with Socket Bracket	
EL7ICANB	90W, without Socket Bracket	







6" Airtight IC Housing Remodel

SPECIFICATIONS



6" Shallow Airtight IC Housing

New Construction

6	-6	
6	. 1	0.0
1 1	. 1	43
10	The and	

6" Shallow Airtight IC Housing Remodel

EL7RICA	Lamp: 90W MAX.


CAT NO.

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

EL7ICA-G24 Lamp: 27W MAX.	CAI NO.	SPECIFICATIONS	
	EL7ICA-G24	Lamp: 27W MAX.	

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.

CAT NO.	SPECIFICATIONS
PP10H	Lamp: 150W MAX



6" Shallow Housing New Construction

7.00
1 4
5

6" Shallow Housing Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

Compatible Products



For use with 6" Trims for PAR Lamps

6" Accessories







ш	re	⊢n	OS.	IIIre



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow. 16" L x 14 3%'

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L