

| Project name: |  |
|---------------|--|
| Fixture type: |  |
| Date:         |  |

# **6" Shower Trim with Fresnel Lens**



#### **Features**

- Shower Trim.
- Lamp: 42W MAX. 4 Pin CFL, 60W MAX A19.
- 8" O.D.

#### **Technical Details**

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.

### **Options**







White

White Lexan

Bronze



Black

#### **Product Numbers**

| Item    | Description         | Finish      |
|---------|---------------------|-------------|
| EL13W   |                     | All White   |
| EL13SH  |                     | White Lexan |
| EL13BZ  |                     | All Bronze  |
| EL13B   |                     | All Black   |
| EL13KSH | with Socket Bracket | White Lexan |

## Product Number Builder Example: EL13W

6" Shower Trim

Socket Bracket

Finish

**EL13** 

no Socket Bracket

K Socket Bracket

W All White

SH White Lexan

BZ All Bronze

**B** All Black

# **Compatible** Products



For use with 6" Trims for PAR Lamps

# 6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

| CAT NO.  | SPECIFICATIONS              |
|----------|-----------------------------|
| EL7ICA   | 90W, with Socket Bracket    |
| EL7ICANB | 90W, without Socket Bracket |



CAT NO. SPECIFICATIONS
EL7FICA 90W



6" Airtight IC Housing Remodel



6" Shallow Airtight IC Housing

New Construction

| 6   | -   |     |
|-----|-----|-----|
| 6   | -   | 100 |
| F F | . 1 |     |
| 100 | 400 | 0 - |

6" Shallow Airtight IC Housing Remodel

| CAI NO. | SPECIFICATIONS |  |
|---------|----------------|--|
| EL7RICA | Lamp: 90W MAX. |  |
|         |                |  |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| R9ICA   | Lamp: 75W MAX. |

| CAT NO. | SPECIFICATIONS |  |
|---------|----------------|--|
| RR9ICA  | Lamp: 75W MAX. |  |



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

| CAT NO.    | SPECIFICATIONS |  |
|------------|----------------|--|
| EL7ICA-G24 | Lamp: 27W MAX. |  |

| CAT NO. | SPECIFICATIONS  |
|---------|-----------------|
| R10H    | Lamp: 150W MAX. |

| CAT NO. | SPECIFICATIONS  |
|---------|-----------------|
| RR10H   | Lamp: 150W MAX. |



6" Shallow Housing New Construction



6" Shallow Housing Remodel

| CAT NO. | SPECIFICATIONS                  |
|---------|---------------------------------|
| R9H     | Lamp: 75W,<br>Medium Base (E26) |

| CAT NO. | SPECIFICATIONS                       |
|---------|--------------------------------------|
| RR9H    | Lamp: 75W MAX.,<br>Medium Base (F26) |

# **Compatible** Products



For use with 6" Trims for PAR Lamps

## 6" Accessories







| - | ire | -r | 10 | $\sim$ | ure |
|---|-----|----|----|--------|-----|
|   |     |    |    |        |     |



Mica Fire Tape

| CAT NO. | SPECIFICATIONS    |
|---------|-------------------|
| FIRECVR | 9 ¾" H × 17" O.D. |

| CAT NO.    | SPECIFICATIONS         |
|------------|------------------------|
| FIREENCL   | 20 3/8" L x 14 3/8" W  |
| FIREENCL-S | Shallow, 16" L x 14 3% |

| CAT NO.  | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W × 16' L |