

Project name:		
Fixture type:		
Date:		

6" Shower Trim with Fresnel Lens



Features

- Shower Trim.
- Lamp: 42W MAX. 4 Pin CFL, 60W MAX A19.
- 8" O.D.

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.



Product Number

Item	Description	Finish
EL13KSH	with Socket Bracket	White Lexan

Product Number Builder Example: EL13W

6" Shower Trim Socket Bracket **Finish EL13** All White no Socket Bracket K Socket Bracket SH White Lexan

BZ All Bronze

All Black

Nickel

Compatible Products



For use with 6" Trims for PAR Lamps

6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket








6" Airtight IC Housing Remodel



6" Shallow Airtight IC Housing

New Construction



6" Shallow Airtight IC Housing Remodel

CAT NO.	SPECIFICATIONS	
EL7RICA	Lamp: 90W MAX.	

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS	
RR9ICA	Lamp: 75W MAX.	



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

CAT NO.	SPECIFICATIONS	
EL7ICA-G24	Lamp: 27W MAX.	

CAT NO.	SPECIFICATIONS	
R10H	Lamp: 150W MAX.	

CAT NO.	SPECIFICATIONS	
RR10H	Lamp: 150W MAX.	



6" Shallow Housing New Construction

6	1	
5	. 1	00
1 1	1	
160	-	

6" Shallow Housing Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

Compatible Products



For use with 6" Trims for PAR Lamps

6" Accessories







Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H × 17" O.D.

CAI NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3%" W

CAT NO.	SPECIFICATIONS
FIRETAPE	³ / ₄ " W × 16' L