

6" Shower Trim with Fresnel Lens



Features

- Shower Trim.
- Lamp: 42W MAX. 4 Pin CFL, 60W MAX A19.
- 8" O.D.

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.

Options



White



White Lexan



Bronze



Black



Nickel

Product Number

Item	Finish
EL13N	Nickel

Product Number Builder Example: EL13W

6" Shower Trim

EL13

Socket Bracket

no Socket Bracket
K Socket Bracket

Finish

W All White
SH White Lexan
BZ All Bronze
B All Black
N Nickel

Compatible Products

For use with 6" Trims for PAR Lamps

6" Line Voltage ICA Housings



6" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket



6" Airtight IC Housing
Double Wall New Construction

CAT NO.	SPECIFICATIONS
EL7IC100A	Lamp: 100W MAX.



6" Airtight IC 2-Hour Fire Rated Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7FICA	90W



6" Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.



6" Shallow Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.



6" Shallow Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.



6" Airtight IC Universal Housing
New Construction

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.



6" Airtight IC Universal Housing
Remodel

CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.



6" Shallow Housing
New Construction

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)



6" Shallow Housing
Remodel

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

Compatible Products

For use with 6" Trims for PAR Lamps

6" Accessories



Fire Cover



Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L