

# 6" Sloped Ceiling Medium Base IC Airtight Remodel Housing

ELCO Slant allows for installation in sloped ceilings ranging from 2/12 (10°) to 6/12 (26.5°). Can be used in insulated ceilings. Fits in 2" x 8" joist construction.




## Features

- Airtight aluminum Single Wall Construction.
- Integral thermal protector guards against improper lamping.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Socket: Medium base E26.
- Compatible with Medium Base Incandescent, CFL or LED Lamp MAX. 75W. Works with LED Quick-Connect Inserts with PSA30 Socket Adapter.

## Specifications

<b>Wattage</b>	75W
<b>Voltage</b>	120V
<b>Lamp Type</b>	Medium Base (E26)
<b>Damp Location</b>	Listed

## Dimensions



## Technical Details

### Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Aluminum housing for greater heat dissipation.

**Installation:** Designed for ceiling plenums where 2x8 joists or taller are used. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and One 3/4" knockout. Four true pry-out knockout slots for easy Romex installation.

### Electrical:

- Rated for 120V or 277V input.
- For 277V step down to 120V housing consult factory.

**Trims:** Compatible with ELCO Line Voltage Slope Trims.

**Listings:** UL Listed for Damp Location.

UL Listed for Direct Contact with Insulation and Combustible Material.

UL Listed for Feed Through.

Meets restricted air flow requirements (Per ASTM E-283 Standard).

## Product Numbers

Item	Lamp type	Watts	Voltage
<b>EL918RICA</b>	Medium Base (E26)	75W	120V