

Project name:	
Fixture type:	
Date:	

6" Specular Reflector Trim



Features

- Reflector.
- Lamp: (1) 42W max CFL, 75W MAX PAR30 or R30.
- O.D.: 7 1/4".

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated LED Housings.

Lamp: Compatible with Medium base (E26) PAR type.

Options





All White

Chrome w/White

Product Numbers

Item	Description	Finish
ELS30W	,	All White
ELS30C	Specular	Chrome with White Trim

Product Number Builder Example: ELS30W

6" Reflector Trim Finish

ELS30

W All White

C Chrome with White Trim

Compatible Products



For use with 6" Trims for PAR Lamps

6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket







6" Airtight IC Housing Remodel



6" Shallow Airtight IC Housing

New Construction

6	The	
6	. 1	0.00
1 \$	- 1	5
100	15	

6" Shallow Airtight IC Housing Remodel

CAT NO.	SPECIFICATIONS	
EL7RICA	Lamp: 90W MAX.	

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS	
RR9ICA	Lamp: 75W MAX.	



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

CAT NO.	SPECIFICATIONS	
EL7ICA-G24	Lamp: 27W MAX.	

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.

CAT NO.	SPECIFICATIONS	
RR10H	Lamp: 150W MAX.	



6" Shallow Housing New Construction

6	The	
10	. 1	00
1 3	-1	4
100	0	

6" Shallow Housing
Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

Compatible Products



For use with 6" Trims for PAR Lamps

6" Accessories







Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS	
FIRECVR	9 ¾" H x 17" O.D.	

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow. 16" L x 14 3%

CAT NO.	SPECIFICATIONS
FIRETAPE	³ / ₄ " W × 16' L