

# 6" Specular Reflector Trim



## Features

- Reflector.
- Lamp: (1) 42W max CFL, 75W MAX PAR30 or R30.
- O.D.: 7 1/4".

## Technical Details

**Construction:** Meticulously manufactured trim with a powder coated or anodized finish.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 6" Integrated LED Housings.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Options



All White



Chrome w/White  
Trim

## Product Numbers

| Item   | Description | Finish                 |
|--------|-------------|------------------------|
| ELS30W |             | All White              |
| ELS30C | Specular    | Chrome with White Trim |

## Product Number Builder Example: ELS30W

6" Reflector Trim

Finish

**ELS30**

- W** All White
- C** Chrome with White Trim

# Compatible Products

For use with 6" Trims for PAR Lamps

## 6" Line Voltage ICA Housings



6" Airtight IC Housing  
**New Construction**

| CAT NO.  | SPECIFICATIONS              |
|----------|-----------------------------|
| EL7ICA   | 90W, with Socket Bracket    |
| EL7ICANB | 90W, without Socket Bracket |



6" Airtight IC Housing  
**Double Wall New Construction**

| CAT NO.   | SPECIFICATIONS  |
|-----------|-----------------|
| EL7IC100A | Lamp: 100W MAX. |




6" Airtight IC 2-Hour Fire Rated Housing  
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL7FICA | 90W            |




6" Airtight IC Housing  
**Remodel**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL7RICA | Lamp: 90W MAX. |




6" Shallow Airtight IC Housing  
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| R9ICA   | Lamp: 75W MAX. |




6" Shallow Airtight IC Housing  
**Remodel**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| RR9ICA  | Lamp: 75W MAX. |



6" Airtight IC Housing with GU24 Base Socket  
**New Construction**

| CAT NO.    | SPECIFICATIONS |
|------------|----------------|
| EL7ICA-G24 | Lamp: 27W MAX. |



6" Airtight IC Universal Housing  
**New Construction**

| CAT NO. | SPECIFICATIONS  |
|---------|-----------------|
| R10H    | Lamp: 150W MAX. |




6" Airtight IC Universal Housing  
**Remodel**

| CAT NO. | SPECIFICATIONS  |
|---------|-----------------|
| RR10H   | Lamp: 150W MAX. |



6" Shallow Housing  
**New Construction**

| CAT NO. | SPECIFICATIONS                  |
|---------|---------------------------------|
| R9H     | Lamp: 75W,<br>Medium Base (E26) |



6" Shallow Housing  
**Remodel**

| CAT NO. | SPECIFICATIONS                       |
|---------|--------------------------------------|
| RR9H    | Lamp: 75W MAX.,<br>Medium Base (E26) |

# Compatible Products

For use with 6" Trims for PAR Lamps

## 6" Accessories

---



Fire Cover



Fire Enclosure



Mica Fire Tape

| CAT NO. | SPECIFICATIONS      |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |

| CAT NO.    | SPECIFICATIONS             |
|------------|----------------------------|
| FIREENCL   | 20 3/8" L x 14 3/8" W      |
| FIREENCL-S | Shallow, 16" L x 14 3/8" W |

| CAT NO.  | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |