

Project name:

Fixture type:

Date:

6" Square Sky Panel™

Edge-Lit LED Technology with glare control lens for even glow




Features

- Fits 3 1/2" and 4" Octagon and Round junction boxes
- Fits 4" and 6" housings with optional ELSPMNT468 mounting accessories
- Dimmable to 10% with select dimmers
- Edge-lit LED technology •
- IC Rated and Wet Location Rated
- ETL Listed
- JA8 2016 E-Compliant
- 6 3/8" Sq. x 5/8" H


Specifications

Wattage	15W
Lumens	900 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Wet Location	Listed

Options



Dimensions



Product Number

Item	Lamp type	Lumens	сст	Watts	Voltage	Dimming	Finish
ELSP66CT5B	LED	900 lm	2700K, 3000K, 3500K, 4000K, 5000K	15W	120V	Triac/ELV	All Black

Product Number Builder Example: ELSP66CT5W

ELSP66	
СТ5 2700К - 5000К	W All White B All Black



Dimmer Compatibility Chart The Sky Panels™ For ELSP12, ELSP22, ELSP43, ELSP63, ELSP66, and ELSP83 Series

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Lutron	Caseta Wireless, 120V AC, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way	PD-6WCL	10% - 100%
	Diva, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	DVCL-153P	10% - 100%
	Skylark, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	CTCL-153P	10% - 100%
	Maestro, 120V, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	MACL-153M	10% - 100%
	Lumea, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	LECL-153P	10% - 100%
Leviton	Trimatron Rotary, 120V AC, 60Hz, 600W Incandescent, Single Pole, 3-Way, Commercial Application	6681	10% - 100%

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross refrence that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.

🔿 amazon alexa	e Google Assistant	<mark>ම</mark> Apple Hor	neKit I N	ΙΝ ΣΤΕΦΝ		LUTRON.	wemo
	2042 E. Vernon Ave. Vernon CA 90058		Tel 323.231.2600 Fax 3		1.3200	elcolighting.com	