

6" Super Sloped Ceiling Medium Base IC Airtight Remodel Housing

ELCO Slant allows for installation in sloped ceilings ranging from 7/12 (30°) to 12/12 (45°). Can be used in insulated ceilings. Fits in 2" x 8" joist construction.




Features

- Airtight aluminum Single Wall Construction.
- Integral thermal protector guards against improper lamping.
- Designed for use in 7/12 to 12/12 sloped ceiling.
- Socket: Medium base E26.
- Compatible with Medium Base Incandescent, CFL or LED Lamp MAX. 75W. Works with LED Quick-Connect Inserts with PSA30 Socket Adapter.

Specifications

| | |
|----------------------|-------------------|
| Wattage | 75W |
| Voltage | 120V |
| Lamp Type | Medium Base (E26) |
| Damp Location | Listed |

Dimensions



Technical Details

Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 7/12 to 12/12 sloped ceiling.
- Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and One 3/4" knockout. Four true pry-out knockout slots for easy Romex installation.

Electrical:

- Rated for 120V or 277V input.
- For 277V step down to 120V housing consult factory.

Trims: Compatible with EL602, EL603, EL604, EL606, EL607, EL608.

Listings: cUL Listed for Damp Location.

cUL Listed for Direct Contact with Insulation and Combustible Material.

cUL Listed for Feed Through.

Meets restricted air flow requirements (Per ASTM E-283 Standard).

Product Numbers

| Item | Lamp type | Watts | Voltage |
|-----------|-------------------|-------|---------|
| EL901RICA | Medium Base (E26) | 75W | 120V |



Dimmer Compatibility Chart LED Sloped Ceiling

ELCO Lighting

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product | Part Number | Dimmed Light Output Range |
|--|--|-------------|---------------------------|
| Eaton | Decorator Single Pole/3-Way dimmer | DLC03P | 10% - 100% |
| Leviton | Decora SureSlide® Single Pole Slide-To-Off with Optional Locator Light | 6631 | 10% - 100% |
| | Decora SureSlide® Single Pole/3-Way with Preset ON/OFF switch and Optional Locator Light | 6633 | 10% - 100% |
| | Universal Decora Dimmable LED, CFL and Incandescent SureSlide Slide Dimmer | 6672 | 10% - 100% |
| | Decora SureSlide® Universal Dimmer | 6674 | 10% - 100% |
| Lutron | Skylark® Contour single pole, incandescent / halogen dimmer | CT-600P | 10% - 100% |
| | Skylark® Contour 3-way, incandescent / halogen "eco-dim" dimmer | CT-603PG | 5% - 85% |
| | Diva® (gloss) single pole, incandescent / halogen, preset dimmer | DV-600P | 10% - 100% |
| | Diva® (gloss) 3-way, incandescent / halogen, preset dimmer | DV-603P | 10% - 100% |
| | Diva® (gloss) C•L single pole/3-way dimmer | DVCL-153P | 5% - 86% |
| | Maestro® C•L single pole/3-way/multi-location dimmer | MACL-153M | 10% - 100% |
| | Skylark® Series Dual Slide-to-Off dimmer | S-2 | 10% - 100% |
| | Skylark® single pole, incandescent/halogen, slide-to-off dimmer | S-600 | 10% - 100% |
| Ariadni®/Toggler® Series 150W Single Pole/3-Way dimmer | TGCL-153P | 5% - 86% | |

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.