

Fixture type: Date:	Project name:
Date:	Fixture type:
	Date:

# **6" Wide Flange Baffle Trim**



#### **Features**

- Baffle.
- Lamp: 75W MAX PAR30 or R30.
- O.D.: 8".

#### **Technical Details**

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.

### **Options**



All White

#### **Product Numbers**

Item	Finish
EL304W	All White

## Product Number Builder Example: EL304W

6" Baffle Trim Finish

EL304

W All White

# **Compatible** Products



For use with 6" Trims for PAR Lamps

# 6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket







6" Airtight IC Housing Remodel

	The state of the s	
		/ =
1		
	N W	

6" Shallow Airtight IC Housing

New Construction

6	-	
5	. 1	00
1 }	- 1	45
100	5	

6" Shallow Airtight IC Housing Remodel

CAI NO.	SPECIFICATIONS	
EL7RICA	Lamp: 90W MAX.	

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS	
RR9ICA	Lamp: 75W MAX.	



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.

CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.



6" Shallow Housing New Construction



6" Shallow Housing Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX., Medium Base (E26)

# **Compatible** Products



For use with 6" Trims for PAR Lamps

## 6" Accessories







H	−ir	е	Er	IC	los	uı	re



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow. 16" L x 14 3%'

CAT NO.	SPECIFICATIONS
FIRETAPE	<sup>3</sup> / <sub>4</sub> " W × 16' L