

# 8" Round Sky Panel™

Edge-Lit LED Technology with glare control lens for even glow



## Features

- Fits 3 1/2" and 4" Octagon and Round junction boxes
- Fits 4" and 6" housings and optional mounting accessories
- Dimmable to 10% with select dimmers
- Edge-lit LED technology
- IC Rated and Wet Location Rated
- ETL Listed
- JA8 2016 E-Compliant, Energy Star Compliant.
- 9" O.D. x 5/8" H

## Specifications

<b>Wattage</b>	18W
<b>Lumens</b>	1150 lm - 1300 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	2700K - 4000K
<b>Dimmable</b>	Triac/ELV
<b>Lamp Type</b>	LED
<b>CRI</b>	90+
<b>Wet Location</b>	listed

## Options




White



Black

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
<b>ELSP8327W</b>	LED	1150 lm	2700K	18W	120V	Triac/ELV	All White
<b>ELSP8327B</b>	LED	1150 lm	2700K	18W	120V	Triac/ELV	All Black
<b>ELSP8330W</b>	LED	1200 lm	3000K	18W	120V	Triac/ELV	All White
<b>ELSP8330B</b>	LED	1200 lm	3000K	18W	120V	Triac/ELV	All Black
<b>ELSP8340B</b>	LED	1300 lm	4000K	18W	120V	Triac/ELV	All Black
<b>ELSP83CT3W</b>	LED	1200 lm	3000K, 3500K, 4000K	18W	120V	Triac/ELV	All White
<b>ELSP83CT3B</b>	LED	1200 lm	3000K, 3500K, 4000K	18W	120V	Triac/ELV	All Black

**Product Number Builder** Example: **ELSP8327W**

---

8" Round Sky Panel™

Color Temp

Finish

**ELSP83**

- 27** 2700K
- 30** 3000K
- 40** 4000K
- CT3** 3000K, 3500K, 4000K

- W** All White
- B** All Black



**ELCO Lighting**

# Dimmer Compatibility Chart

## The Sky Panels™

For ELSP12, ELSP22, ELSP43, ELSP63, ELSP66,  
and ELSP83 Series

### For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Lutron	Caseta Wireless, 120V AC, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way	PD-6WCL	10% - 100%
	Diva, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	DVCL-153P	10% - 100%
	Skylark, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	CTCL-153P	10% - 100%
	Maestro, 120V, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	MACL-153M	10% - 100%
	Lumea, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	LECL-153P	10% - 100%
Leviton	Trimatron Rotary, 120V AC, 60Hz, 600W Incandescent, Single Pole, 3-Way, Commercial Application	6681	10% - 100%

**\*NOTE: Refer to dimmer manufacturer’s documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com