

8" Square Sky Panel™

Edge-Lit Technology with glare control lens for even glow



Features

- Fits 3 1/2" and 4" Octagon and Round Junction boxes
- Fits 4" and 6" Housings with optional mounting accessories
- Dimmable to 10% with select dimmers
- Edge-lit LED technology with glare control lens
- IC Rated and Wet Location Rated
- ETL Listed
- JA8 2016 E-Compliant

Specifications

Wattage	18W
Lumens	1200 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV
Lamp Type	LED

Options




White



Black

Dimensions



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ELSP88CT5W	LED	1200 lm	2700K, 3000K, 3500K, 4000K, 5000K	18W	120V	Triac/ELV	All White
ELSP88CT5B	LED	1200 lm	2700K, 3000K, 3500K, 4000K, 5000K	18W	120V	Triac/ELV	All Black

Product Number Builder Example: ELSP88CT5W

8" Square Sky Panel™

CCT

Finish

ELSP88

CT5 2700K - 5000K

W All White


B All Black

8" Square Sky Panel

Multiplier: 3000K (x 0.92)

PHOTOMETRIC REPORT

Product #: ELSP8840
 Wattage/Lumens: 19.5W/ 1175 lm
 Luminaire LPW: 60Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	419
5	412
15	399
25	365
35	321
45	268
55	202
65	135
75	67
85	0
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	26.2	11.7'
6'	11.6	17.5'
8'	6.54	23.4'
10'	4.19	29.2'

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30°	323.71	27.60
0-40°	530.87	45.20
0-60°	938.11	79.90
0-90°	1174.71	100.00