

Birch™ 8"-10" Round Reflector Trim

The sleek and clean looking Birch™ System Trims will blend seamlessly into your commercial space. The trims offer a light source aperture of 2 5/8" and a deep reflector that delivers smooth and abundant light distribution with minimal glare.



Features

- Self-flanged spun aluminum reflector
- Twist-On system for easy installation to Birch™ Modules
- Spring loaded mounting clips to hold them tightly into the ceiling

Technical Details

Installation: Easy to install with Twist-On mechanism to any of our Birch System modules. Spring loaded mounting clips will hold the trim tightly into the ceiling.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Options




White



All Haze (semi-specular)

Dimensions



Product Numbers

| Item | Finish |
|---------|--------------------------|
| ELB810W | All White |
| ELB810H | All Haze (Semi-Specular) |

Product Number Builder Example: ELB810W

Birch™ 8" Round Reflector Trim

Finish

ELB810


- W** All White
- H** All Haze (Semi-Specular)

Compatible Products



For use with **Birch™ Trims**


Birch™ LED Modules



Birch™ Pro LED Module with 5-CCT Switch (750 lm - 1500 lm)




| CAT NO. | COLOR TEMPERATURE | SPECIFICATIONS |
|--------------|--|--|
| ELB15RCT5ICA | 5-CCT Switch 2700K, 3000K, 3500K, 4000K, 5000K | <ul style="list-style-type: none"> • IC Rated, for use in IC and Non-IC applications • 750 lm - 1500 lm (10W - 20W) • Beam Angle adjustment from 25°-45° • 120/277V input with 0-10V dimming |



Birch™ High Lumen LED Module (1250 lm - 3000 lm)



| CAT NO. | COLOR TEMPERATURE | SPECIFICATIONS |
|----------|-------------------|---|
| ELB30R30 | 3000K | <ul style="list-style-type: none"> • Non-IC, for use in Non-IC applications • 1250 lm - 3000 lm (13W - 30W) |
| ELB30R35 | 3500K | <ul style="list-style-type: none"> • Beam Angle adjustment from 22°-50° |
| ELB30R40 | 4000K | <ul style="list-style-type: none"> • 120/277V input with 0-10V dimming |




Birch™ High Lumen LED Module (3200 lm - 5000 lm)




| CAT NO. | COLOR TEMPERATURE | SPECIFICATIONS |
|----------|-------------------|--|
| ELB50R30 | 3000K | <ul style="list-style-type: none"> • Non-IC, for use in Non-IC applications • 3200 lm - 5000 lm (32W - 55W) |
| ELB50R35 | 3500K | <ul style="list-style-type: none"> • Beam Angle adjustment from 22°-50° |
| ELB50R40 | 4000K | <ul style="list-style-type: none"> • 120/277V input with 0-10V dimming • Works with 6" & 8" Trims (ELB610 & ELB810 only) |


4", 6", & 8" Birch™ Architectural Frames



4" Architectural Commercial Frame
New Construction



6" Architectural Commercial Frame
New Construction



8" Architectural Commercial Frame
New Construction

| CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS |
|------------|------------------------------|------------|------------------------------|------------|------------------------------|
| ELB4EH | Frame (hanger bars required) | ELB6EH | Frame (hanger bars required) | ELB8EH | Frame (hanger bars required) |
| ELB4EH-EM5 | with Emergency Backup | ELB6EH-EM5 | with Emergency Backup | ELB8EH-EM5 | with Emergency Backup |

Hanger Bars
for **Birch™**
Architectural
Frames

27" **Flat Hanger Bars**
for Wood Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| FB27 | Set of 2 |



26" **C-Channel Hanger Bars**
for T-Bar Ceilings

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| CH26 | Set of 2 |




Compatible Products




For use with **Birch™ Trims**


4", 6", & 8" Birch™ Plaster Frames



4" Plaster Commercial Frame
New Construction



6" Plaster Commercial Frame
New Construction



8" Plaster Commercial Frame
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------|
| ELB4PF | Frame |
| ELB4PF-EM5 | with Emergency Backup |


| CAT NO. | SPECIFICATIONS |
|------------|-----------------------|
| ELB6PF | Frame |
| ELB6PF-EM5 | with Emergency Backup |

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------|
| ELB8PF | Frame |
| ELB8PF-EM5 | with Emergency Backup |

Remodel & Retrofit Birch™ Applications

Remodel/Retrofit

| CAT NO. | SPECIFICATIONS |
|------------|-----------------------|
| ELBRMD | Remodel |
| ELBRMD-EM5 | with Emergency Backup |



Retrofit

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| ELBRT | Retrofit |

