

Birch™ Remodel/Retrofit



Features

- Add architectural downlighting to an existing ceiling.
- Compatible with all sizes Birch™ trims and modules
- Encased Quick Connector for easy module installation
- Optional 90 minutes Emergency Battery Backup

Technical Details

Installation: Designed to be installed in existing holes for retrofitting less efficient lighting technologies.

Junction Box: Positioned to accommodate straight conduit runs. 1/2" trade size conduit knockouts.


Warranty: ELCO Products are built to last. 5-year Limited warranty.

Options



Optional Battery Backup

Dimensions



Product Number

Item	Description
ELBRMD	Remodel/Retrofit

Product Number Builder Example: **ELBRMD**

Birch™ Remodel/Retrofit

Optional

ELBRMD

No Battery Backup


-EM5 Emergency Battery Backup

Compatible Products




For use with **Birch™ Remodel & Retrofits**


Birch™ LED Modules



Birch™ Pro LED Module with 5-CCT Switch (750 lm - 1500 lm)




CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB15RCT5ICA	5-CCT Switch 2700K, 3000K, 3500K, 4000K, 5000K	<ul style="list-style-type: none"> • IC Rated, for use in IC and Non-IC applications • 750 lm - 1500 lm (10W - 20W) • Beam Angle adjustment from 25°-45° • 120/277V input with 0-10V dimming



Birch™ High Lumen LED Module (1250 lm - 3000 lm)



CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB30R30	3000K	<ul style="list-style-type: none"> • Non-IC, for use in Non-IC applications • 1250 lm - 3000 lm (13W - 30W) • Beam Angle adjustment from 22°-50° • 120/277V input with 0-10V dimming
ELB30R35	3500K	
ELB30R40	4000K	



Birch™ High Lumen LED Module (3200 lm - 5000 lm)




CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB50R30	3000K	<ul style="list-style-type: none"> • Non-IC, for use in Non-IC applications • 3200 lm - 5000 lm (32W - 55W) • Beam Angle adjustment from 22°-50° • 120/277V input with 0-10V dimming • Works with 6" & 8" Trims (ELB610 & ELB810 only)
ELB50R35	3500K	
ELB50R40	4000K	

4", 6", & 8" Birch™ Twist-On Trims



4" Round Reflector

CAT NO.	SPECIFICATIONS
ELB410W	All White
ELB410BB	All Black
ELB410H	All Haze (Semi-Specular)
ELB410HW	Haze/White Trim




4" Square Reflector Trim

CAT NO.	SPECIFICATIONS
ELB440W	All White
ELB440BB	All Black
ELB440H	All Haze (Semi-Specular)
ELB440HW	Haze/White Trim



6" Round Reflector

CAT NO.	SPECIFICATIONS
ELB610W	All White
ELB610BB	All Black
ELB610H	All Haze (Semi-Specular)
ELB610HW	Haze/White Trim



6" Round Adjustable Reflector

CAT NO.	SPECIFICATIONS
ELB629W	All White
ELB629B	All Black
ELB629H	All Haze (Semi-Specular)

• Not compatible with ELB50R Module Series



8" Round Reflector

CAT NO.	SPECIFICATIONS
ELB810W	All White
ELB810H	All Haze (Semi-Specular)