

Birch™ Retrofit



Features


- To convert an existing fixture to a Birch™ fixture
- Compatible with all sizes Birch™ trims and modules
- Encased Quick Connector for easy module installation

Technical Details

Installation: Designed to add Birch™ System downlighting to an existing commercial application with a junction box on site.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Dimensions




Product Numbers

Item	Description
ELBRT	Retrofit

Compatible Products

For use with **Birch™ Remodel & Retrofits**

Birch™ LED Modules



Birch™ Pro LED Module with 5-CCT Switch (750 lm - 1500 lm)

CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB15RCT5ICA	5-CCT Switch 2700K, 3000K, 3500K, 4000K, 5000K	<ul style="list-style-type: none"> • IC Rated, for use in IC and Non-IC applications • 750 lm - 1500 lm (10W - 20W) • Beam Angle adjustment from 25°-45° • 120/277V input with 0-10V dimming



Birch™ High Lumen LED Module (1250 lm - 3000 lm)

CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB30R30	3000K	<ul style="list-style-type: none"> • Non-IC, for use in Non-IC applications • 1250 lm - 3000 lm (13W - 30W) • Beam Angle adjustment from 22°-50° • 120/277V input with 0-10V dimming
ELB30R35	3500K	
ELB30R40	4000K	

4", 6", & 8" Birch™ Twist-On Trims



4" Round Reflector

CAT NO.	SPECIFICATIONS
ELB410W	All White
ELB410H	All Haze



6" Round Reflector

CAT NO.	SPECIFICATIONS
ELB610W	All White
ELB610H	All Haze



8" Round Reflector

CAT NO.	SPECIFICATIONS
ELB810W	All White
ELB810H	All Haze