

Project name:

Fixture type:

Date:

Birch™ Retrofit



Features


- To convert an existing fixture to a Birch $^{\scriptscriptstyle \rm M}$ fixture
- Compatible with all sizes Birch[™] trims and modules
- Encased Quick Connector for easy module installation

Technical Details

Installation: Designed to add Birch m System downlighting to an existing commercial application with a junction box on site.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Dimensions



Product Number

| Item | Description |
|-------|-------------|
| ELBRT | Retrofit |

Compatible Products

CAT NO.

ELB15RCT5ICA



.........

UHE Switch

For use with Birch™ Remodel & Retrofits

Birch[™] LED Modules

| E E |
|-----|
| |
| - |



| CAT NO. | COLOR TEMPERATURE | SPECIFICATIONS |
|----------|-------------------|---|
| ELB30R30 | 3000K | Non-IC, for use in Non-IC applications |
| ELB30R35 | 3500K | 1250 lm - 3000 lm (13W - 30W) Beam Angle adjustment from 22°-50° |
| ELB30R40 | 4000K | 120/277V input with 0-10V dimming |

Birch™ Pro LED Module with 5-CCT Switch (750 Im - 1500 Im) CCTswick

COLOR TEMPERATURE

2700K, 3000K, 3500K,

5-CCT Switch

4000K, 5000K

Birch" High Lumen LED Module (3200 lm - 5000 lm) (Ull : Switch)

Birch[™] High Lumen LED Module (1250 Im - 3000 Im) (UILEI Switch)

| ALL CONTRACTOR | CAT NO. | COLOR TEMPERATURE | SPECIFICATIONS |
|---------------------------|----------|-------------------|--|
| Contraction of the second | ELB50R30 | 3000K | • Non-IC, for use in Non-I |
| | ELB50R35 | 3500K | 3200 lm - 5000 lm (32) Beam Angle adjustmen |
| | ELB50R40 | 4000K | • 120/277V input with 0-1 |

| | COLOR TEMPERATURE | SPECIFICATIONS |
|-----|-------------------|---|
| 830 | 3000K | Non-IC, for use in Non-IC applications |
| 835 | 3500K | 3200 lm - 5000 lm (32W - 55W) Beam Angle adjustment from 22°-50° |
| 840 | 4000K | 120/277V input with 0-10V dimming |

SPECIFICATIONS

· 750 lm - 1500 lm (10W - 20W)

Beam Angle adjustment from 25°-45°

120/277V input with 0-10V dimming

Works with 6" & 8" Trims (ELB610 & ELB810 only)

· IC Rated, for use in IC and Non-IC applications

4", 6", & 8" Birch[™] Twist-On Trims



4" Round Reflector

| CAT NO. | SPECIFICATIONS |
|----------|-----------------------------|
| ELB410W | All White |
| ELB410BB | All Black |
| ELB410H | All Haze (Semi-Specular) |
| ELB410HW | Haze/White Trim |

Not compatible with ELB50R Module Series



4" Square Reflector Trim

| + oquare iterector min | |
|-----------------------------|--|
| SPECIFICATIONS | |
| AllWhite | |
| All Black | |
| All Haze (Semi-Specular) | |
| Haze/White Trim | |
| | |



6" Round Reflector

| o Round Reneetor | | 0 |
|------------------|-----------------------------|-----|
| CAT NO. | SPECIFICATIONS | C |
| ELB610W | All White | E |
| ELB610BB | All Black | E |
| ELB610H | All Haze (Semi-Specular) | E |
| ELB610HW | Haze/White Trim | • N |



6" Round Adjustable Reflector

| CAT NO. | SPECIFICATIONS |
|--|-----------------------------|
| ELB629W | All White |
| ELB629B | All Black |
| ELB629H | All Haze (Semi-Specular) |
| Not compatible with ELB50R Module Series | |



8" Round Reflector

| CAT NO. | SPECIFICATIONS |
|---------|-----------------------------|
| ELB810W | AllWhite |
| ELB810H | All Haze (Semi-Specular) |