

# Commercial Construction E.L.L. LED Module




## Features

- Module used with E.L.L Commercial Housing for 0-10V dimming and/or Emergency battery back-up options
- Smooth lens provides even lighting illuminations
- Works in 4" and 6" housing with twist-&-lock trims
- Excellent color rendering 93+ CRI
- Patent Pending
- Beam angles are 60° standard and 10°, 25°, 36° optional.

## Specifications

<b>Wattage</b>	11.8/13.7W
<b>Lumens</b>	850/1100 lm
<b>Color Temp.</b>	2700K
<b>Lamp Type</b>	LED

## Dimension



## Technical Details

**Construction:** Module used with E.L.L Commercial Construction Housings. Die-cast module houses the LED chip, reflector, diffuser, and heat sink.

**Installation:** Twist-&-lock System allows easy installation on wide variety of trims options. Must be installed with Commercial Construction E.L.L. Housings. See installation sheet for detailed information.

**Electrical:** For use with External Driver, Module: 35.5VDC.

**Trims:** Compatible with our variety of trims.

**Dimmability:** Smooth and even dimming. 0-10V/Triac/ELV dimming. Sunset option dims from 3000K to 1800K

## Product Number

Item	Lamp type	Lumens	CCT	Watts
ELL2127D	LED	850/1100 lm	2700K	11.8/13.7W

## Product Number Builder Example: ELL2127D

E.L.L. LED Module	Lumens	Color Temperature	Beam Angle
<b>ELL</b>	<b>21</b> 850/1100	<b>27D</b> 2700K <b>30D</b> 3000K <b>35D</b> 3500K <b>40D</b> 4000K <b>SDD</b> Sunset	<b>60°</b> Standard <b>F</b> 36° <b>N</b> 25° <b>S</b> 10°