

Darby LED Standard Lumen Decorative Flush Mount Lights




Features

- White polycarbonate lens.
- Contemporary double ring design.
- Fully assembled and easy to install.
- Suitable for qualified hard wire installation into a standard 4x4 junction box.
- UL listed for damp location.
- ENERGY STAR. CA Title 24 compliant (JA8-2016).

Specifications

| | |
|----------------------|-----------|
| Wattage | 14W |
| Lumens | 1075 lm |
| Voltage | 120V |
| Color Temp. | 4000K |
| Dimmable | Triac/ELV |
| Lamp Type | LED |
| CRI | 90+ |
| Damp Location | Listed |

Size Chart



| Size | Diameter | Height |
|------|----------------------------------|---------------------------------|
| 10" | 9 ⁷ / ₈ " | 2 ³ / ₄ " |
| 12" | 12 ¹ / ₈ " | 3 ³ / ₈ " |
| 14" | 14 ¹ / ₈ " | 3 ³ / ₄ " |
| 16" | 16 ¹ / ₈ " | 4 ³ / ₈ " |
| 18" | 18 ¹ / ₈ " | 4 ³ / ₄ " |

Product Number

| Item | Description | Lamp type | Lumens | CCT | Watts | Voltage | Dimming | Finish |
|-----------|-------------|-----------|---------|-------|-------|---------|-----------|--------|
| ELD11040W | 10" | LED | 1075 lm | 4000K | 14W | 120V | Triac/ELV | Nickel |

Product Number Builder Example: ELD11030W

| ELCO LED Flush Mount | Diameter | Color Temp. | Finish |
|----------------------|------------------------------------------------------------------|-------------------------------------------------------------|-----------------|
| ELD1 | 10 10" 12 12" 14 14" 16 16" | 30 3000K 40 4000K CT5 2700-5000K | W Nickel |



ELCO Lighting

Dimmer Compatibility Chart

Ceiling Mounts

Darby & Dustin

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product | Part Number | Dimmed Light Output Range |
|--------------|-----------------------------------------------------|-------------|---------------------------|
| Leviton | - | 1A3306 | 10% - 100% |
| | - | 1G1306 | 10% - 100% |
| | - | 1K2306 | 10% - 100% |
| Lutron | Diva Single Pole/3-Way Incandescent/Halogen Dimmer | DVW-603P | 10% - 100% |
| | Diva Single Pole Incandescent/Halogen Preset Dimmer | DV-600P | 10% - 100% |
| | Maestro C•L Single Pole/3-Way/Multi-Location Dimmer | MACL-153M | 7% - 100% |
| | Maestro Single Pole Timer Dimmer | MA-T51H | 10% - 100% |

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.