

# Darby LED Standard Lumen Decorative Flush Mount Lights




## Features

- White polycarbonate lens.
- Contemporary double ring design.
- Fully assembled and easy to install.
- Suitable for qualified hard wire installation into a standard 4x4 junction box.
- UL listed for damp location.
- ENERGY STAR. CA Title 24 compliant (JA8-2016).

## Specifications

<b>Wattage</b>	26W
<b>Lumens</b>	2050 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	4000K
<b>Dimmable</b>	Triac/ELV
<b>Lamp Type</b>	LED
<b>CRI</b>	90+
<b>Damp Location</b>	Listed

## Size Chart



Size	Diameter	Height
10"	9 <sup>7</sup> / <sub>8</sub> "	2 <sup>3</sup> / <sub>4</sub> "
12"	12 <sup>1</sup> / <sub>8</sub> "	3 <sup>3</sup> / <sub>8</sub> "
14"	14 <sup>1</sup> / <sub>8</sub> "	3 <sup>3</sup> / <sub>4</sub> "
16"	16 <sup>1</sup> / <sub>8</sub> "	4 <sup>3</sup> / <sub>8</sub> "
18"	18 <sup>1</sup> / <sub>8</sub> "	4 <sup>3</sup> / <sub>4</sub> "

## Product Number

Item	Description	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ELD11640W	16"	LED	2050 lm	4000K	26W	120V	Triac/ELV	Nickel

## Product Number Builder Example: ELD11030W

ELCO LED Flush Mount	Diameter	Color Temp.	Finish
<b>ELD1</b>	<b>10</b> 10" <b>12</b> 12" <b>14</b> 14" <b>16</b> 16"	<b>30</b> 3000K <b>40</b> 4000K <b>CT5</b> 2700-5000K	<b>W</b> Nickel



**ELCO Lighting**

# Dimmer Compatibility Chart

## Ceiling Mounts

Darby & Dustin

### For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Leviton	-	1A3306	10% - 100%
	-	1G1306	10% - 100%
	-	1K2306	10% - 100%
Lutron	Diva Single Pole/3-Way Incandescent/Halogen Dimmer	DVW-603P	10% - 100%
	Diva Single Pole Incandescent/Halogen Preset Dimmer	DV-600P	10% - 100%
	Maestro C•L Single Pole/3-Way/Multi-Location Dimmer	MACL-153M	7% - 100%
	Maestro Single Pole Timer Dimmer	MA-T51H	10% - 100%

\*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.