

# Electronic Dimmable LED Driver (Large)

For tape lights and general applications




## Features

- Large electronic dimmable LED driver.
- 48W - 96W
- 120V AC, 60Hz
- Triac dimmable
- ETL listed

## Specifications

<b>Wattage</b>	48W - 96W
<b>Voltage</b>	12V (4A) or 24V (4A)
<b>Dimmable</b>	Triac

## Dimensions



## Product Numbers

Item	Description	Watts	Voltage	Dimming
<b>DRVE12V48DW</b>	Electronic Dimmable LED Driver	48W	12V (4A)	Triac
<b>DRVE12V60DW</b>	Electronic Dimmable LED Driver	60W	12V (5A)	Triac
<b>DRVE12V96DW</b>	Electronic Dimmable LED Driver	96W	12V (8A)	Triac
<b>DRVE24V48DW</b>	Electronic Dimmable LED Driver	48W	24V (2A)	Triac
<b>DRVE24V60DW</b>	Electronic Dimmable LED Driver	60W	24V (2.5A)	Triac
<b>DRVE24V96DW</b>	Electronic Dimmable LED Driver	96W	24V (4A)	Triac



**ELCO Lighting**

# Dimmer Compatibility Chart

## Electronic LED Drivers

For DRVE24V24DW, DRVE24V48DW,  
DRVE24V60DW, & DRVE24V96DW

### For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Cooper	120 AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, Residential Application	S106P	10% - 100%
Leviton	Decora® Slide, 120V, 600W Incandescent, Single Pole	6621	10% - 100%
	Decora® Slide, 120V, 60Hz, 600W Incandescent/Halogen or 150W LED/CFL, Single Pole	6672	10% - 100%
	Decora® Slide, 120V, 60Hz, 600W Incandescent or 300W LED/CFL, Single Pole, 3-Way, Indoor Application	DSL06-1LZ	10% - 100%
	Decora® Slide, 120V, 60Hz, 600W Incandescent, Single Pole, 3-Way	IPL006-IOZ	10% - 100%
Lutron	Caséta, 120V, 600W Incandescent/Halogen or 150W LED/CFL, Single Pole, 3-Way	PD-6WCL	10% - 100%
	Diva®, 120V, 60Hz, 600W Incandescent/Halogen or 150W LED/CFL, Single Pole, 3-Way	DVCL-153P	10% - 100%
	Skylark, 120V, 60Hz, Fluorescent Applications, Single Pole, 3-Way	SFTU-5A3P	10% - 100%
	120/277V AC, 0-10V LED/CFL Ballast, Single Pole, 3-Way, Indoor Application	DMD-LED3-021	10% - 100%
	Skylark, 120V, 60Hz, 600W Incandescent/Halogen or 150W LED/CFL, Single Pole, 3-Way, Indoor Application	CTCL-153P	10% - 100%
	Diva®, 120V, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, Commercial/Residential Application	DV-600P	10% - 100%

**\*NOTE: Refer to dimmer manufacturer’s documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com