

# Incandescent Step Light with Louvered Faceplate



## Features

- Galvanized stamped steel housing, powder coated.
- Lamp: Type A or T10 40W max medium base included.
- Thermal device included.
- Hole Cutout: 8 5/8"W x 3 7/8"H.
- cUL listed for damp location.
- For indoor use.

## Specifications

|                  |                   |
|------------------|-------------------|
| <b>Wattage</b>   | 40W               |
| <b>Voltage</b>   | 120V              |
| <b>Lamp Type</b> | Medium Base (E26) |

## Options



White





Black



Bronze

## Dimensions



## Product Number

| Item           | Lamp type         | Watts | Voltage | Finish    |
|----------------|-------------------|-------|---------|-----------|
| <b>ELST42B</b> | Medium Base (E26) | 40W   | 120V    | All Black |



**ELCO Lighting**

# Dimmer Compatibility Chart Incandescent/CFL Step Lights

For ELST42, ELST43, ELST49, & ELST52

## For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product  | Part Number            | Dimmed Light Output Range |
|--------------|--|------------------------|---------------------------|
| Lutron       | Skylark Contour, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way Indoor Application, Residential/Commercial Application | CT-603PG / CT-600PR    | 10% - 100%                |
|              | Diva, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, Residential/Commercial Application                               | DV-600PR / DV603PG     | 10% - 100%                |
|              | Diva, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way  | DVW-603PGH / DVCL-153P | 10% - 100%                |
|              | Maestro, 120V, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way  | MACL-153M / TGCL-153P  | 10% - 100%                |
|              | Skylark, Single Pole 600W Incandescent/Halogen, Slide-to-Off Dimmer  | S-600PR / S-2-LH       | 10% - 100%                |
| Leviton      |  | 1A1505 / IC1605        | 10% - 100%                |
|              | SureSlide, 120V AC 60Hz, 600W for LED and CFL, 600W for Incandescent, Single Pole, 3-Way, Polycarbonated Housing                     | 6631 / 6633            | 10% - 100%                |
| Cooper       | Decorator Dimmer, 120V 60Hz, 300W for LED and CFL, 600W for Incandescent, Single Pole, 3-Way, Polycarbonated Housing                 | DLC03P                 | 10% - 100%                |

**\*NOTE: Refer to dimmer manufacturer’s documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 [elcolighting.com](http://elcolighting.com)